

CORDLESS

DRILLING/
IMPACT DRILLING/
FASTENINGROTARY/
DEMOLITIONCUTTING
[CONCRETE/
MASONRY/
METAL]

MULTI TOOL

GRINDING

SANDING

SAWING

PLANERS/
ROUTERSNIBBLERS/
SHEARS

PNEUMATIC

DUST
EXTRACTION/
HEATGUN/
LASERGARDEN/
AGRICULTURAL
TOOLSPETROL
ENGINE TOOLS**9554HN 115mm (4-1/2")****325** **Angle Grinder****710W**
MOTOR**Compact yet powerful one-hand grinder.**

- Small circumference barrel grip for easy handling.
- Labyrinth construction prevents all ball bearings from dust and debris.
- Armature coated with protective zig zag varnish and field coated with powder varnish to protect the motor from dust and wire breakage, ensuring durability enough for masonry cutting.

Specifications:-

Continuous rating input	710 W
Capacity	Depressed center wheel: 115 mm (4-1/2") Abrasive disc: 115 mm (4-1/2") Diamond wheel: 115 mm (4-1/2")
No load speed	10,000 rpm
Dimensions (L x W x H)	258mm x 129mm x 106mm (10-1/8" x 5-1/8" x 4-3/16")
Spindle thread	DIN type
Net weight	1.8 kg (4.1 lbs)
Power supply cord	2.5 m (8.2 ft)

Standard Equipment: Depressed Center Wheel, Lock Nut Wrench, Grip.**GA4530 115mm (4-1/2")****459** **Angle Grinder****720W**
MOTOR**TO BE DISCONTINUED****Small circumference barrel grip and ergonomically designed side grip angle for easy handling.**

- Labyrinth construction protects all ball bearings from dust and debris.
- High quality motor with excellent heat-resistance.
- Small gear housing provides easy handling and high maneuverability.
- Motor field coated with protective powder varnish to protect from dust.

Specifications:-

Continuous rating Input	720W
Capacity	Depressed center wheel: 115mm (4-1/2") Abrasive disc: 115mm (4-1/2") Diamond wheel: 115mm (4-1/2")
No load speed	11,000rpm
Dimensions (L x W x H)	266 x 128 x 103mm (10-1/2" x 5" x 4-1/16")
Spindle thread	DIN type
Net weight	1.8kg (4.0lbs)
Power supply cord	2.5m (8.2ft)

Standard Equipment: Depressed Center Wheel, Lock Nut Wrench, Side Grip.**9557HN 115mm (4-1/2")****325** **Angle Grinder****840W**
MOTOR**High performance motor with enough power for masonry cutting and high heat resistance.**

- Labyrinth construction protects all ball bearings from dust and debris.
- Small circumference barrel grip for easy handling.
- Shaft lock for easy wheel changes.
- Easier repairing of gear section assembled with key.

Specifications:-

Continuous rating Input	840W
Capacity	Depressed center wheel: 115mm (4-1/2") Abrasive disc: 115mm (4-1/2") Diamond wheel: 115mm (4-1/2")
No load speed	11,000rpm
Dimensions (L x W x H)	271mm x 129mm x 106mm (10-5/8" x 5-1/8" x 4-3/16")
Spindle thread	DIN type
Net weight	2.0kg (4.4lbs)
Power supply cord	2.5m (8.2ft)

Standard Equipment: Depressed Center Wheel, Lock Nut Wrench, Grip.**9557HP 115mm (4-1/2")****325** **Angle Grinder****840W**
MOTOR**Ergonomic paddle switch featured.**

- Natural fit slim body to left and right hand for easy handling.
- Ergonomically designed paddle lever gives comfort to the fingers.
- Lock-off button built in the center of paddle lever.

Specifications:-**Dead Man Switch**

Continuous rating Input	840W
Capacity	Depressed center wheel: 115mm (4-1/2") Abrasive disc: 115mm (4-1/2") Diamond wheel: 115mm (4-1/2")
No load speed	11,000rpm
Dimensions (L x W x H)	273mm x 129mm x 106mm (10-3/4" x 5-1/8" x 4-3/16")
Spindle thread	DIN type
Net weight	2.1kg (4.5lbs)
Power supply cord	2.5m (8.2ft)

Standard Equipment: Depressed Center Wheel, Lock Nut Wrench, Grip.