

**XR502 S3 SRC**



NYLON MESH/NUBUCK LEATHER SHOES - S3 HRO SRC

Ref. XR502S3



Product specifications

Upper: Nubuck leather and nylon mesh, S3 water resistant treatment. Lining: Polyamide absorbing. Insock: Removable preformed - Polyamide on EVA. Midsole: Cemented - PU with shock absorber Panoshock®. Outsole: Rubber. Non metallic shoe.

**COLOUR**

Black

**SIZE**

39, 41, 42, 43, 44, 45, 46, 47

Product Use - Risks



Antistatic



Slip



Heat



Shock



PERFORATION



Second work / craftman



Light industry



Services / Logistics

## Product's highlights & user's benefits



### PU/RUBBER CEMENTED OUTSOLE

- 1- Flex-Zone
- 2- Antislip rubber
- 3- TPU foot arch reinforcement



### Speed lace



- Composite toe cap 200- joule,
- Lighter than steel
- Non conductive material



### NON-METALLIC



- Ultra flexible anti-perforation composite insole



- PANOSHOCK® system
- For reduced fatigue & added comfort

### DELTA INNOVATION



### COMPOSITE

## Certifications and Standards



REGULATION (EU) 2016/425

EN ISO 20344:2011 Personal protective equipment - Test methods for footwear



EN ISO 20345:2011 Personal protective equipment - Safety footwear.  
S3 HRO: Additional special requirements  
SRC: Slip resistance

### USA STANDARDS



ASTM F 2413:2011 Standard Specification for Performance Requirements for Protective (Safety) Toe Cap Footwear.  
M I/75 C/75 PR SD: Additional special requirements

## References

References	Bar code	COLOUR	SIZE		
XR502S3NO39	3295249195137	Black	39	5	-
XR502S3NO41	3295249195229	Black	41	5	-
XR502S3NO42	3295249195250	Black	42	5	-
XR502S3NO43	3295249195267	Black	43	5	-
XR502S3NO44	3295249195274	Black	44	5	-
XR502S3NO45	3295249195298	Black	45	5	-
XR502S3NO46	3295249195311	Black	46	5	-
XR502S3NO47	3295249195328	Black	47	5	-