

VENICUT 52



HEATNOCUT® KNITTED GLOVE - LATEX-COATED PALM

Rif. VECUT52



Caratteristiche prodotto

HEATnocut® high performance polyethylene fibre. Latex coating on palm and fingertips. Gauge 10.

Support: HEATnocut® fibre (high performance synthetic fibres).

Coating : 100% latex.

COLOUR

Yellow-Black

SIZE

07, 08, 09, 10

Utilizzi prodotto - Rischi



Heat



CUTTING



Wearing



Construction / Civil engineering



Heavy industry



Light industry



Services / Logistics



Wind energy

I PLUS del prodotto – Benefici utente



Latex coating

Good resistance to abrasion
Rough finish for excellent grip on handled objects

HEATnocut® High Performance Polyethylene

Contact heat (250°C for 15 seconds) and cut resistance
Very good level of abrasion resistance



Cut level D

Certificazioni - Norme



REGULATION (EU) 2016/425

EN420:2003+A1:2009 General requirements

3: Dexterity (from 1 to 5)

EN388:2016 Protective gloves against mechanical Risks (Levels obtained on the palm)

3: Resistance to abrasion (from 1 to 4)

X: Resistance to cutting (from 1 to 5)

4: Resistance to tear (from 1 to 4)

2: Resistance to puncture (1 to 4)

D: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)



EN407:2004 Protective gloves against Heat & Fire risks (X = Unrealized test)

2: Contact heat resistance (from 1 to 4)

X: Convective heat resistance (1 to 4)

X: Radiant heat resistance (from 1 to 4)

X: Small splashes of molten metal (from 1 to 4)

X: Large quantities of molten metal (from 1 to 4)





USA STANDARDS



ANSI-ISEA 105:2016 Hand protection

A3: Resistance to cutting by sharp objects (from A1 to A9)

Riferimenti

Riferimenti	Codice a barre	COLOUR	SIZE		
VECUT5207	3295249150778	Yellow-Black	07	60	12
VECUT5208	3295249158484	Yellow-Black	08	60	12
VECUT5209	3295249150785	Yellow-Black	09	60	12
VECUT5210	3295249150792	Yellow-Black	10	60	12