CHEMSAFE VV835

GLOVE IN NITRILE ON POLYAMIDE LINING - FOAM NITRILE COATING PALM - 35 CM

Ref. VV835

Product specifications

Double nitrile coating on polyamide lining. Third rough foam nitrile coating on palm and fingertips. Length: 35 cm. Thickness: 1.15 mm on cuff - 1.30 mm on palm.

Support: 100% polyamide.
Coating: Nitrile.

COLOUR
Green

SIZE
08, 09, 10, 11

DELTA PLUS GROUP - ZAC La Peyrolière - BP 140 - 84405 Apt cedex FRANCE- Tel :+33 (0)4 90 74 20 33 - Fax :+33 (0)4 90 74 32 59
E.mail :information@deltaplus.fr - Web : www.deltaplus.eu

1

![DELTAPLUS YOUR SAFETY AT WORK]

Product Use - Risks

BIOLOGICAL   Wearing   CHEMICAL

PARTICULES

Heavy industry   Light industry   Oil / Gas

Agriculture / Green areas

CHEM D-FINDER

Product's highlights & user's benefits

> 1,15 MM

0% LATEX

Rough structure palm		Very good grip	
Triple nitrile coating		Good resistance to abrasion	
100% polyamide support		Very good comfort	

DELTA PLUS GROUP - ZAC La Peyrolière - BP 140 - 84405 Apt cedex FRANCE- Tel :+33 (0)4 90 74 20 33 - Fax :+33 (0)4 90 74 32 59
E.mail :information@deltaplus.fr - Web : www.deltaplus.eu

2

Certifications and Standards

$$C \, \epsilon$$

REGULATION (EU) 2016/425

EN420:2003+A1:2009 General requirements
    5: Dexterity (from 1 to 5)

EN388:2016 Protective gloves against mechanical Risks (Levels obtained on the palm)
    4: Resistance to abrasion (from 1 to 4)
    1: Resistance to cutting (from 1 to 5)
    2: Resistance to tear (from 1 to 4)
    1: Resistance to puncture (1 to 4)
    X: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)

EN ISO 374-1:2016 Protective gloves against dangerous chemicals and micro- organisms - Part 1: Terminology and performance requirements for chemical risks.
  TYPE B: Type B - Water and air tightness according to EN ISO 374-2:2019. Permeation resistance to at least 3 chemicals at level 2 according to EN16523-1: 2015 (from 1 to 6).
    .: Determination of resistance to degradation by chemicals according to EN ISO 374-4: 2019. Part 4: Determination of resistance to degradation by chemicals.
  A 2 > 30 mn: Méthanol (A) CAS 67-56-1
  J 3 > 60 mn: n-Heptane (J) CAS 142-85-5
  K 5 > 240 mn: Caustic soda 40% (K) CAS 1310-73-2
  L 2 > 30 mn: Sulphuric acid 96 % (L) CAS 7664-93-9

EN ISO 374-5:2016 Protective gloves against dangerous chemicals and micro-organisms - Part 5: Terminology and performance requirements against micro- organisms risks.
  BACTERIA + FUNGI .: BACTERIA + FUNGI : Water and air tightness according to EN ISO 374-2:2019.

References

References	Bar code	COLOUR	SIZE	📦	🏺
VV835VE08	3295249202866	Green	08	60	6
VV835VE09	3295249202873	Green	09	60	6
VV835VE10	3295249202880	Green	10	60	6
VV835VE11	3295249202897	Green	11	60	6

DELTA PLUS GROUP - ZAC La Peyrolière - BP 140 - 84405 Apt cedex FRANCE- Tel :+33 (0)4 90 74 20 33 - Fax :+33 (0)4 90 74 32 59
E.mail :information@deltaplus.fr - Web : www.deltaplus.eu

3