

Data sheet collection: Pressure independent control valves

Datasheet HERZ PICV, Issue 0320

General information

This product is only intended for the purpose intended by the manufacturer. This also includes compliance with all associated product regulations. Changes or conversions are not permitted.

Disposal

Local and currently applicable legislation must be observed for disposal.

Note

All schemes are symbolic in nature and do not claim to be complete.

Materials note

Pursuant to Article 33 of the REACH Regulation (EC No. 1907/2006), we are obliged to point out that the material lead is listed on the SVHC list and that all brass components manufactured in our products exceed 0.1% (w / w) lead (CAS: 7439-92-1 / EINECS: 231-100-4). Since lead is a component part of an alloy, actual exposure is not possible and therefore no additional information on safe use is necessary.


All specifications and statements within this document are according to information available at the time of printing and meant for informational purpose only. Herz Armaturen reserves the right to modify and change products as well as its technical specifications and/or its functioning according to technological progress and requirements. It is understood that all images of Herz products are symbolic representations and therefore may visually differ from the actual product. Colours may differ due to printing technology used. In case of any further questions don't hesitate to contact your closest HERZ Branch-office.

HERZ Pressure independent control valves


Datasheet **4006** 1x, 2x, 4x, 6x; **4206** 1x, 2x, 4x, 6x

Dimensions in mm

1 4006 XX




1 4206 XX



Dimensions in mm

☑ 1 4006 XX SMART

☑ 1 4206 XX SMART



☑ Installation dimensions and order numbers

| | Order number | DN | Thread, inch | L, mm | H1, mm | H2, mm | H*, mm | B1, mm | B2, mm | L1, mm | L2, mm | M, mm | |
|---------------------|-----------------|-------|--------------|----------------------|--------|--------|--------|--------|--------|--------|--------|-------|----|
| with test points | 1 4006 20 SMART | 15 LF | MT | 3/4 G | 75 | 35 | 69 | 158,8 | 50 | 23 | 41 | 34 | 28 |
| | 1 4006 21 SMART | 15 | | 3/4 G | 75 | 35 | 69 | 158,8 | 50 | 23 | 41 | 34 | 28 |
| | 1 4006 22 SMART | 20 | | 1 G | 75 | 32 | 73 | 159,8 | 50 | 23 | 41 | 34 | 28 |
| | 1 4006 30 SMART | 15 LF | | 3/4 flat sealing | 75 | 35 | 69 | 158,8 | 50 | 23 | 41 | 34 | 28 |
| | 1 4006 31 SMART | 15 | | 3/4 flat sealing | 75 | 35 | 69 | 158,8 | 50 | 23 | 41 | 34 | 28 |
| | 1 4006 32 SMART | 20 | | 1 G flat sealing | 75 | 32 | 73 | 159,8 | 50 | 23 | 41 | 34 | 28 |
| | 1 4006 39 SMART | 15MF | | 3/4 flat sealing | 75 | 35 | 69 | 158,8 | 50 | 23 | 41 | 34 | 28 |
| | 1 4006 72 SMART | 20 HF | | 1 G flat sealing | 75 | 32 | 73 | 159,8 | 50 | 23 | 41 | 34 | 28 |
| | 1 4006 29 SMART | 15 MF | | 3/4 G | 75 | 35 | 69 | 158,8 | 50 | 23 | 41 | 34 | 28 |
| without test points | 1 4006 60 SMART | 15 LF | MT | 3/4 G | 75 | 35 | 69 | 158,8 | 26 | 23 | 41 | 34 | 28 |
| | 1 4006 61 SMART | 15 | | 3/4 G | 75 | 35 | 69 | 158,8 | 26 | 23 | 41 | 34 | 28 |
| | 1 4006 62 SMART | 20 | | 1 G | 75 | 32 | 73 | 159,8 | 26 | 23 | 41 | 34 | 28 |
| | 1 4006 82 SMART | 20HF | | 1 G flat sealing | 75 | 32 | 73 | 159,8 | 26 | 23 | 41 | 34 | 28 |
| | 1 4006 69 SMART | 15 MF | | 3/4 G | 75 | 35 | 69 | 158,8 | 26 | 23 | 41 | 34 | 28 |
| with test points | 1 4006 11 | 15 | MT | 3/4 G | 66 | 59 | 75 | 188,8 | 74 | 54 | 45 | 94 | 28 |
| | 1 4006 12 | 20 | | 1 G | 76 | 60 | 75 | 189,8 | 72 | 56 | 45 | 89 | 28 |
| | 1 4006 13 | 25 | | 5/4 G flat sealing | 76 | 60 | 75 | 189,8 | 72 | 56 | 45 | 89 | 28 |
| | 1 4006 14 | 32 | | 1 1/2 G flat sealing | 114 | 76 | 86 | 216,8 | 76 | 47 | 57 | 86 | 28 |
| | 1 4006 15 | 40 | | 1 3/4 G flat sealing | 132 | 86 | 97 | 237,8 | 82 | 47 | 66 | 85 | 28 |
| | 1 4006 16 | 50 | | 2 3/8 G flat sealing | 140 | 86 | 97 | 237,8 | 82 | 47 | 70 | 85 | 28 |
| without test points | 1 4006 41 | 15 | MT | 3/4 G | 66 | 59 | 75 | 188,8 | 74 | 47 | 45 | 94 | 28 |
| | 1 4006 42 | 20 | | 1 G | 76 | 60 | 75 | 189,8 | 72 | 47 | 45 | 89 | 28 |
| | 1 4006 43 | 25 | | 5/4 G flat sealing | 76 | 60 | 75 | 189,8 | 72 | 47 | 45 | 89 | 28 |
| | 1 4006 44 | 32 | | 1 1/2 G flat sealing | 114 | 76 | 86 | 216,8 | 76 | 47 | 57 | 86 | 28 |
| | 1 4006 45 | 40 | | 1 3/4 G flat sealing | 132 | 86 | 97 | 237,8 | 82 | 47 | 66 | 85 | 28 |
| | 1 4006 46 | 50 | | 2 3/8 G flat sealing | 140 | 86 | 97 | 237,8 | 82 | 47 | 70 | 85 | 28 |
| with test points | 1 4206 20 SMART | 15 LF | FT | 1/2 | 75 | 35 | 67 | 156,8 | 50 | 23 | 41 | 34 | 28 |
| | 1 4206 21 SMART | 15 | | 1/2 | 75 | 35 | 65 | 154,8 | 50 | 23 | 41 | 34 | 28 |
| | 1 4206 22 SMART | 20 | | 3/4 | 75 | 35 | 65 | 154,8 | 50 | 23 | 41 | 34 | 28 |
| | 1 4206 72 SMART | 20 HF | | 3/4 | 75 | 35 | 65 | 154,8 | 50 | 23 | 41 | 34 | 28 |
| | 1 4206 29 SMART | 15 MF | | 1/2 | 75 | 35 | 67 | 156,8 | 50 | 23 | 41 | 34 | 28 |
| without test points | 1 4206 60 SMART | 15 LF | FT | 1/2 | 75 | 35 | 67 | 156,8 | 26 | 23 | 41 | 34 | 28 |
| | 1 4206 61 SMART | 15 | | 1/2 | 75 | 35 | 65 | 154,8 | 26 | 23 | 41 | 34 | 28 |
| | 1 4206 62 SMART | 20 | | 3/4 | 103 | 32 | 71 | 157,8 | 26 | 23 | 41 | 34 | 28 |
| | 1 4206 82 SMART | 20HF | | 3/4 | 103 | 32 | 71 | 157,8 | 26 | 23 | 41 | 34 | 28 |
| | 1 4206 69 SMART | 15 MF | | 1/2 | 102 | 35 | 67 | 156,8 | 26 | 23 | 41 | 34 | 28 |
| with test points | 1 4206 11 | 15 | FT | 1/2 | 66 | 59 | 73 | 186,8 | 74 | 54 | 45 | 94 | 28 |
| | 1 4206 12 | 20 | | 3/4 | 76 | 60 | 73 | 187,8 | 72 | 56 | 45 | 89 | 28 |
| | 1 4206 13 | 25 | | 1 | 90 | 60 | 73 | 187,8 | 72 | 56 | 45 | 89 | 28 |
| | 1 4206 14 | 32 | | 1 1/4 | 114 | 76 | 84 | 214,8 | 76 | 47 | 57 | 86 | 28 |
| | 1 4206 15 | 40 | | 1 1/2 | 132 | 86 | 95 | 235,8 | 82 | 47 | 66 | 85 | 28 |
| | 1 4206 16 | 50 | | 2 | 140 | 86 | 95 | 235,8 | 82 | 47 | 70 | 85 | 28 |
| | 1 4206 41 | 15 | FT | 1/2 | 66 | 59 | 73 | 186,8 | 47 | 74 | 45 | 94 | 28 |

| | | | | | | | | | | | | |
|---------------------|-----------|----|-------|-----|----|----|-------|----|----|----|----|----|
| without test points | 1 4206 42 | 20 | 3/4 | 76 | 60 | 73 | 187,8 | 47 | 72 | 45 | 89 | 28 |
| | 1 4206 43 | 25 | 1 | 90 | 60 | 73 | 187,8 | 47 | 72 | 45 | 89 | 28 |
| | 1 4206 44 | 32 | 1 1/4 | 114 | 76 | 84 | 214,8 | 47 | 76 | 57 | 86 | 28 |
| | 1 4206 45 | 40 | 1 1/2 | 132 | 86 | 95 | 235,8 | 47 | 82 | 66 | 85 | 28 |
| | 1 4206 46 | 50 | 2 | 140 | 86 | 95 | 235,8 | 47 | 82 | 70 | 85 | 28 |

* with 1 7990 3X actuator


Technical specifications

| | DN15 | | 15LF | 15MF | DN20 | DN20 | 20HF | DN25 | DN32 | DN40 | DN50 |
|---|---|-----------|-------------|--------------|--------|------------------|--------|--------|--------|--------|------------|
| 1 4006 ..; 1 4206 .. | 11; 41 | 21; 61 | 20;60 30 | 29; 69 39 | 12; 42 | 22 ; 62 32 | 72; 82 | 13; 43 | 14; 44 | 15; 45 | 16 ; 46 |
| k _{vs} -value | 1,01 | 0,57 | 0,22 | 0,36 | 2 | 1,16 | 3,2 | 3,26 | 5,59 | 9,49 | 9 , 17 |
| Flowrate @ 100% setting, [l/h] | 430 | 400 | 120 | 190 | 900 | 820 | 1750 | 1900 | 2500 | 5200 | 4820 |
| Operating pressure | max. 16 bar (4006) max. 25 bar (4206, 4006HF) | | | | | | | | | | |
| Max. differential pressure over the valve | 6 bar | | | | | | | | | | |
| Min. operating temperature | 2 °C (pure water); - 20 °C (antifreeze) | | | | | | | | | | |
| Max. operating temperature | till DN32: 130 °C DN40 - DN50: 110 °C | | | | | | | | | | |
| Stroke | 4 mm | | | | | | | | | | |
| Control range | See above, flowrate @ 100% setting | | | | | | | | | | |
| Water quality | Water purity in accordance with the ÖNORM H 5195 and VDI 2035 standards Ethylene and propylene glycol can be mixed to a ratio of 25 - 50 vol. [%]. | | | | | | | | | | |

The integrated control unit together with the actuating drive is responsible for modular control. Various actuating drives might be used (see also chapter: Accessories and spare parts).

Materials

| N | Description | Materials |
|----|------------------|------------------------|
| 1 | Housing | DZR brass CC770S |
| 2 | Membrane housing | brass CW602N |
| 3 | Pin | stainless steel 14301 |
| 4 | Membrane | EPDM |
| 5 | O-Rings | EPDM |
| 6 | Spring | spring steel |
| 7 | capillary pipe | copper Cu-DHP (CW024A) |
| 8 | Pin | stainless steel 14301 |
| 9 | Spring | spring steel |
| 10 | Protective cap | plastic |



Water purity in accordance with the ÖNORM H5195 and VDI 2035 standards

The use of ethylene and propylene glycol in a mixture ratio of 25 - 50% by volume [%] is permitted. Ammonia contained in hemp damages

brass valve housings. EPDM seals are swollen by mineral oils or lubricants containing mineral oil and thus lead to failure of the EPDM seals. For frost and corrosion protection agents based on ethylene and propylene glycol can be found in the manufacturer's documentation.

Pursuant to Article 33 of the REACH Regulation (EC No. 1907/2006), we are obliged to point out that the material lead is listed on the SVHC list and that all brass components manufactured in our products exceed 0.1% (w / w) lead (CAS: 7439-92-1 / EINECS: 231-100-4). Since lead is a component part of an alloy, actual exposure is not possible and therefore no additional information on safe use is necessary.

Field of application


The Pressure Independent Balancing Control Valve (PIBCV) is used in all heating and cooling systems with circulation pumps. The valve automatically maintains flow to the required part of the system at the set rate by measuring and immediately adjusting to any variation in pressure. No additional measurements are necessary and the correct flow rate is achieved at all operating conditions. The diaphragm responds to the pressure upstream and downstream of the regulating valve (via an internal impulse line). The valve settings directly affect the volumetric flow through the valve. It is thus possible to set the maximum flow rate based on the flow chart when the valve is fitted. This allows for the balancing of heating circuits, cooling water systems, ceiling cooling and heating panels, air heaters, etc. without any need to first assess the pressure variations in the system. The valve's principal application is as a control valve for terminal units.

System flushing

If it is necessary to flush the system in the direction opposite to the direction of valve's operation, it is important to take into account the maximum allowed differential pressure on the valve for backflushing, equal to 300 kPa. It is also recommended not to exceed the value of the backwash flow more than 3 times the nominal flow rate of the valve.

Installation

The installation takes place in the return, the installation position does not matter. The direction of flow is indicated in the direction of the arrow on the housing. It is recommended to install a shut-off valve before and after the combination valve. The combination valve is shut off with the HERZ setting tool (1 4006 02). The desired flow rate is set in% of the maximum flow rate. Shut off by turning to the right to the stop (display <0% red area).





Application field

It is assumed that a consumer needs a volume flow of 300 l/h. The setting value is searched for the HERZ combination valve 4006 DN 15 (1 4006 21/61/11/41). The maximum flow at valve DN 15 is 400 l/h, that

corresponds to the setting $\frac{300 \text{ l/h}}{400 \text{ l/h}} \times 100 \% = 75 \%$
100%:

The 300 l/h is required thus presetting is 75%, which must be set on the valve. A control measurement is then to be carried out. Please note that a minimum differential pressure according to the data sheet must be available for correct operation on the valve.

The HERZ combi valve 4006 is operated with 2-point or continuously acting actuators. However, continuous control is always recommended. The reason for this is that constant and energy-saving control is essential for fast-working systems such as cooling systems or air heaters. Maximum energy savings can only be achieved with regulating valves.

With continuous control, the volume flow is controlled continuously with the slightest fluctuations between minimum and maximum flow. The continuous control also protects all other system-specific components, right down to the pump. The 2-point control is recommended for slow systems such as underfloor heating.


HERZ 4006 PICVs have several advantages over conventional series connection of volume flow controller and differential pressure controller, since the volume flow controller limits the flow depending on the differential pressure of the system, while the differential pressure is variable. If the amount of water is reduced when the room temperature is reached, the differential pressure increases. The resulting operating point is completely different from that of hydraulic balancing. This means that valves connected in series interfere with themselves.

The valve authority for the HERZ combination valve is ideally "1". A valve authority below 0.3 is an ON / OFF control. In order to ensure the efficiency of your system and proper operation, modular control with an authority greater than 0.5 should be aimed for. Since the HERZ valve 4006 compensates for the different differential pressures, the volume flow to the consumer is kept constant. An over or under supply of the individual consumers is therefore excluded.

Hydraulic balancing is always a relevant topic in building technology. The combination valves 4006, 4006 SMART and 4206, 4206 SMART enable the construction of a technical building system with reduced planning effort.

For systems with a large number of PICVs installed, the use of a differential pressure control valves 4002 is recommended to avoid noise problems, the occurrence of water hammer and an unstable system operation.

Application example




Combi valves are used in fan coil heat supply systems. A combination valve is installed in the return of each fan coil and acts as regulating valve.

Diagram of a four-pipes fan coil heat supply system (extract)

- 1, 2 - shut-off valve STRÖMAX-A 4115;
- 3 - strainer 4111;
- 4 - PICV 4006 SMART;
- 5 - 7990 thermal actuators; 6 - electronic continuous controller.

PICVs in use with a hydraulic distributor.



- 1 - PICV 4006; 2 - 7990 thermal actuator; 3 - hydraulic distributor;
- 4 - shut-off valve STRÖMAX-A 4115;
- 5 - line regulating valve STRÖMAX-GM 4217; 6 - THERMOFLEX 4119 boiler fill and drain valve;
- 7 - strainer 4111; 8 - circulation pump; 9 - electronic continuous controller; 10 - heating water temperature sensor; 11 - Outside temperature sensor.

Valve selection


Select the valve with the smallest dimension that guarantees the necessary nominal flow with an additional safety surcharge. The setting should be as open as possible.

The flow rate calculation is based on the following formula:

$$V = \frac{3600 \times Q}{c \times \rho \times \Delta T} \times 1000, [l/h]$$






V ... volume flow [l / h] Q ... heat output [kW]
 c ... specific heat capacity 4.19 [kJ / kgK] ρ ... density of water [kg / m³]
 ΔT ... temperature difference flow and return [K]

With the help of the kv diagram, the respective minimum differential pressure [kPa] can be determined depending on the flow [l / h] and the default setting [%].







Accessories and spare parts






| Order number | Description | Image |
|--------------|--|---|
| 1 7990 31 | HERZ actuating drive for continuous control M 28 x 1.5, 0..10 V, 5 mm stroke, adapter M 28 x 1.5 colour blue integrated, male connector, cable loose, without limit switch. Closing force 100 N, 1.2 watt. |  |
| 1 7990 32 | HERZ actuating drive for continuous control M 28 x 1.5, 0..10 V, 6.5 mm stroke, adapter M 28 x 1.5 colour blue integrated, male connector, cable loose, without limit switch. Closing force 125 N, 1.2 watt with valve stroke detection. | |
| 1 7708 53 | HERZ actuating drive for 2-point control for floor heating circuit distributors and valves M 28 x 1.5, 2-point, also suitable for pulse-pause operation, 5 mm stroke, adapter M 28 x 1.5 colour red integrated, cable fixed, without limit switch. Closing force 100 N. Power consumption 1 watt. |  |
| 1 7708 52 | HERZ actuating drive for 2-point control for floor heating circuit distributors and valves M 28 x 1.5, 2-point, also suitable for pulse-pause operation, 5 mm stroke, adapter M 28 x 1.5 colour red integrated, cable fixed, without limit switch. Closing force 100 N. Power consumption 1 watt. |  |
| 1 7708 40 | HERZ geared motor 3-point Adapter M 28 x 1.5 colour blue integrated, 24 V, stroke distance max. 8.5 mm, max. actuation force 200 N. |  |
| 1 7708 41 | HERZ geared motor 3-point Adapter M 28 x 1.5 colour blue integrated, 230 V, stroke distance max. 8.5 mm, max. actuation force 200 N. |  |

| | | |
|-----------|--|--|
| 1 7708 42 | HERZ geared motor DDC 0–10 V Adapter M 28 x 1.5 colour blue integrated, 24 V, stroke distance max. 8.5 mm, max. actuation force 200 N. | |
| 1 7708 46 | HERZ geared motor DDC 0–10 V Adapter M 28 x 1.5 colour blue integrated, 24 V, stroke distance max. 8.5 mm, max. actuation force 200 N. With valve port detection and feedback channel. | |

Accessories

| Order number | Dim. | Description | Model |
|--------------|------|---|---|
| 1 0284 01 | 1/4" | Quick test point for combi valve - pressure-independent control valve, brass version, blue cap (return) for pressure transducer. |  |
| 1 0284 02 | 1/4" | Quick test point for combi valve - pressure-independent control valve, brass version, red cap (supply) for pressure transducer |  |
| 1 0284 11 | 1/4" | Quick test point for combi valve - pressure-independent control valve. brass version, blue cap (return) for pressure transducer, extended design for valves with an insulation thickness up to 40 mm. |  |
| 1 0284 12 | 1/4" | Quick test point for combi valve - pressure-independent control valve. brass version, red cap (supply) for pressure transducer, extended design for valves with an insulation thickness up to 40 mm |  |




| | | | |
|-----------|-------|---|---|
| 1 0284 05 | 1 /8" | Quick test point for combi valve - pressure-independent control valve SMART, brass version, blue cap (return) for pressure transducer |  |
| 1 0284 06 | 1 /8" | Quick test point for combi valve - pressure-independent control valve SMART, brass version, red cap (supply) for pressure transducer |  |
| 1 4006 02 | | Pre-setting key HERZ Combi valve pressureindependent control valve for 4006/4206 |  |

Pressetting

The respective setting of the control unit is clearly shown in percentages. The valve is preset with the HERZ setting key (1 4006 02). The desired flow is set in% of the maximum flow. To shut off, turn to the right to <0% (red area).

$$VE [\%] = (\text{Desired flow} / \text{maximum flow}) * 100$$

open = anticlockwise close = clockwise




1 4006 02



How to perform a flow measurement:

- Connect the measuring computer to the measuring nipple
- Enter the dimensions, valve type and setting -> display flow


 **Warning notices**

The valves must be installed for the correct application using clean fittings. A HERZ strainer (4111) should be fitted to prevent impurities

Test points

Two test points are fitted on the same side of the valve and factory sealed. Thanks to this arrangement they are easily accessible and measurement devices can be quickly fitted, no matter in what position the valve has been installed.

| | |
|-------------------------|-------------------|
| HERZ - Standard diagram | HERZ - PICV SMART |
| 1 4006 41 / 1 4206 41 | DN 15 |



| | |
|-------------------------|--|
| HERZ - Standard diagram | |
| | |


1 4006 11 / 1 4206 11


HERZ - Standard diagram


HERZ - PICV SMART
DN 15

1 4006 61 / 1 4206 61

1 4006 21 / 1 4206 21 / 1 4006 31 / 1 4206 31 / 1 4006 41 / 1 4206 41 / 1 4006 51 / 1 4206 51 / 1 4006 61 / 1 4206 61 / 1 4006 71 / 1 4206 71 / 1 4006 81 / 1 4206 81 / 1 4006 91 / 1 4206 91 / 1 4006 101 / 1 4206 101 / 1 4006 111 / 1 4206 111 / 1 4006 121 / 1 4206 121 / 1 4006 131 / 1 4206 131 / 1 4006 141 / 1 4206 141 / 1 4006 151 / 1 4206 151 / 1 4006 161 / 1 4206 161 / 1 4006 171 / 1 4206 171 / 1 4006 181 / 1 4206 181 / 1 4006 191 / 1 4206 191 / 1 4006 201 / 1 4206 201 / 1 4006 211 / 1 4206 211 / 1 4006 221 / 1 4206 221 / 1 4006 231 / 1 4206 231 / 1 4006 241 / 1 4206 241 / 1 4006 251 / 1 4206 251 / 1 4006 261 / 1 4206 261 / 1 4006 271 / 1 4206 271 / 1 4006 281 / 1 4206 281 / 1 4006 291 / 1 4206 291 / 1 4006 301 / 1 4206 301 / 1 4006 311 / 1 4206 311 / 1 4006 321 / 1 4206 321 / 1 4006 331 / 1 4206 331 / 1 4006 341 / 1 4206 341 / 1 4006 351 / 1 4206 351 / 1 4006 361 / 1 4206 361 / 1 4006 371 / 1 4206 371 / 1 4006 381 / 1 4206 381 / 1 4006 391 / 1 4206 391 / 1 4006 401 / 1 4206 401 / 1 4006 411 / 1 4206 411 / 1 4006 421 / 1 4206 421 / 1 4006 431 / 1 4206 431 / 1 4006 441 / 1 4206 441 / 1 4006 451 / 1 4206 451 / 1 4006 461 / 1 4206 461 / 1 4006 471 / 1 4206 471 / 1 4006 481 / 1 4206 481 / 1 4006 491 / 1 4206 491 / 1 4006 501 / 1 4206 501 / 1 4006 511 / 1 4206 511 / 1 4006 521 / 1 4206 521 / 1 4006 531 / 1 4206 531 / 1 4006 541 / 1 4206 541 / 1 4006 551 / 1 4206 551 / 1 4006 561 / 1 4206 561 / 1 4006 571 / 1 4206 571 / 1 4006 581 / 1 4206 581 / 1 4006 591 / 1 4206 591 / 1 4006 601 / 1 4206 601 / 1 4006 611 / 1 4206 611 / 1 4006 621 / 1 4206 621 / 1 4006 631 / 1 4206 631 / 1 4006 641 / 1 4206 641 / 1 4006 651 / 1 4206 651 / 1 4006 661 / 1 4206 661 / 1 4006 671 / 1 4206 671 / 1 4006 681 / 1 4206 681 / 1 4006 691 / 1 4206 691 / 1 4006 701 / 1 4206 701 / 1 4006 711 / 1 4206 711 / 1 4006 721 / 1 4206 721 / 1 4006 731 / 1 4206 731 / 1 4006 741 / 1 4206 741 / 1 4006 751 / 1 4206 751 / 1 4006 761 / 1 4206 761 / 1 4006 771 / 1 4206 771 / 1 4006 781 / 1 4206 781 / 1 4006 791 / 1 4206 791 / 1 4006 801 / 1 4206 801 / 1 4006 811 / 1 4206 811 / 1 4006 821 / 1 4206 821 / 1 4006 831 / 1 4206 831 / 1 4006 841 / 1 4206 841 / 1 4006 851 / 1 4206 851 / 1 4006 861 / 1 4206 861 / 1 4006 871 / 1 4206 871 / 1 4006 881 / 1 4206 881 / 1 4006 891 / 1 4206 891 / 1 4006 901 / 1 4206 901 / 1 4006 911 / 1 4206 911 / 1 4006 921 / 1 4206 921 / 1 4006 931 / 1 4206 931 / 1 4006 941 / 1 4206 941 / 1 4006 951 / 1 4206 951 / 1 4006 961 / 1 4206 961 / 1 4006 971 / 1 4206 971 / 1 4006 981 / 1 4206 981 / 1 4006 991 / 1 4206 991 / 1 4006 1001 / 1 4206 1001










| | |
|-------------------------|--|
| HERZ - Standard diagram | |
|-------------------------|--|

1 4006 12 / 1 4206 12





| | |
|--|-------------|
| HERZ - Standard diagram | HERZ - PICV |
| 1 4006 13 / 1 4206 13 1 4006 43 / 1 4206 43 | DN 25 |





HERZ - Standard diagram

HERZ - PICV

1 4006 14 / 1 4206 14
 1 4006 44 / 1 4206 44

DN 32





| | |
|--|-------------|
| HERZ - Standard diagram | HERZ - PICV |
| 1 4006 16 / 1 4206 16 1 4006 46 / 1 4206 46 | DN 50 |

