



Dimensions in mm

Materials

Body	(1) Ductile Iron/GJS 500-7
Wedge	(2) Ductile Iron/GJS 500-7
Stem	(3) Stainless Steel
Gasket	(4) EPDM
Bonnet	(5) Ductile Iron
O-Ring	(6) NBR
Washer	(7) Brass CZ122
Bushing	(8) Brass
Handwheel	(9) CS
Gland	(10) Ductile Iron
Cap	(11) Ductile Iron



ORDER Number	DN	L	H1	H2	øD1	Flange				
						øD	øk	øg	b	N-ød
4 4113 71	65	190	258	280	180	185	145	118	18	4-ø19
4 4113 72	80	203	293	311	180	200	160	132	18	8-ø19
4 4113 73	100	229	326	340	200	220	180	156	18	8-ø19
4 4113 74	125	254	377	386	250	250	210	184	18	8-ø19
4 4113 75	150	267	414	430	250	285	240	211	18	8-ø23
4 4113 76	200	292	510	550	300	340	295	266	18	12-ø23
4 4113 77	250	330	585	625	350	405	355	319	19	12-ø28
4 4113 78	300	356	663	703	350	460	410	370	21	12-ø28
4 4113 79	350	381	890	955	450	520	470	429	26.5	16-ø28
4 4113 80	400	406	970	1040	450	580	525	480	28	16-ø31
4 4113 81	450	432	1025	1105	450	640	585	520	30	20-ø31
4 4113 82	500	457	1153	1235	450	715	650	609	31.5	16-ø34
4 4113 83	600	508	1310	1395	450	840	770	720	36	20-ø37

Specification

Temperature range	: -10°C ... +80°C
Pressure rate	: PN16
Flange Dimensions	: according to EN1092-2
Design standard	: BS 5163; EN1074-2; BS 1171
Coating	: 250 µm epoxy coated

For hot and cold water systems for fluids excluding acid and flammable fluids.
The use of ethylene or propylene glycol in a mixing ratio 25- 50% is allowed.



All specifications and information within this document are reflecting the information available at the time of going to print and meant for informational purpose only. Herz Armaturen reserves the right to modify and change products as well as its technical specifications and/or its function according to technological progress and requirements. All diagrams are indicative in nature and do not to be complete. It is understood that all images of Herz products are symbolic representations and therefore may visually differ from the actual product. Colours may differ due to printing technology used. In case of any further questions don't hesitate to contact your closest HERZ Branch-Office.