

## VENICUT50



HEATNOCUT KNITTED GLOVE - COWHIDE LEATHER PALM

Ref. VECUT50



### Product specifications

HEATnocut high performance polyethylene fibre. Cowhide leather on palm and fingertips. Gauge 10.

Support: HEATnocut fibre (high performance synthetic fibres).  
Split cowhide.

#### COLOUR

Yellow-Grey

#### SIZE

09, 10

### Product Use - Risks



Heat



CUTTING



Wearing



Construction / Civil engineering



Heavy industry



Light industry



Services / Logistics



Oil / Gas



Mining

## Product's highlights & user's benefits



HEATnocut High Performance Polyethylene

Contact heat (250°C for 15 seconds) and cut resistance  
Very good level of abrasion resistance

Split leather

Reinforced abrasion resistance  
Suitable for heavy work



Cut level D

## Certifications and Standards



### REGULATION (EU) 2016/425

EN420:2003+A1:2009 General requirements

1: Dexterity (from 1 to 5)

EN388:2016 Protective gloves against mechanical Risks (Levels obtained on the palm)

4: Resistance to abrasion (from 1 to 4)

X: Resistance to cutting (from 1 to 5)

4: Resistance to tear (from 1 to 4)

3: Resistance to puncture (1 to 4)

D: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)



EN407:2004 Protective gloves against Heat & Fire risks (X = Unrealized test)

X: Resistance to flammability (from 1 to 4)

1: Contact heat resistance (from 1 to 4)

X: Convective heat resistance (1 to 4)

X: Radiant heat resistance (from 1 to 4)

X: Small splashes of molten metal (from 1 to 4)

X: Large quantities of molten metal (from 1 to 4)



EN ISO 21420:2020 General requirements



EN388:2016+A1:2018 Protective gloves against mechanical Risks (Levels obtained on the palm)



EN407: 2020 Protective gloves against Heat & Fire risks (X = Unrealized test)



### USA STANDARDS



ANSI-ISEA 105:2016 Hand protection

A4: Resistance to cutting by sharp objects (from A1 to A9)

## References

References	Bar code	COLOUR	SIZE		
VECUT5009	00	Yellow-Grey	09	60	12
VECUT5010	3295249157296	Yellow-Grey	10	60	12