

VENICUT 55



HEATNOCUT® KNITTED GLOVE

Ref. VECUT55



Product specifications

HEATnocut® high performance polyethylene fibre. Gauge 10.

HEATnocut® fibre (high performance synthetic fibres).

COLOUR

Yellow-Grey

SIZE

07, 09, 10

Product Use - Risks



Heat



CUTTING



Wearing



Construction / Civil engineering



Heavy industry



Light industry

Product's highlights & user's benefits



HEATnocut® high performance polyethylene

Contact heat (100°C for 15 seconds) and cut resistance
Very good level of abrasion resistance



Food compatibility



Cut level C

Certifications and Standards



REGULATION (EU) 2016/425

EN420:2003+A1:2009 General requirements

5: Dexterity (from 1 to 5)

EN388:2016 Protective gloves against mechanical Risks (Levels obtained on the palm)



2: Resistance to abrasion (from 1 to 4)

X: Resistance to cutting (from 1 to 5)

4: Resistance to tear (from 1 to 4)

X: Resistance to puncture (1 to 4)

C: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)

EN407:2004 Protective gloves against Heat & Fire risks (X = Unrealized test)



X: Resistance to flammability (from 1 to 4)

1: Contact heat resistance (from 1 to 4)

X: Convective heat resistance (1 to 4)

X: Radiant heat resistance (from 1 to 4)

X: Small splashes of molten metal (from 1 to 4)

X: Large quantities of molten metal (from 1 to 4)



REGULATION (EU) 1935/2004 CONTACT WITH FOOD PRODUCTS

GLOB MIGR Food contact - Overall Migration

.. Contact with wet or watery food

.. Contact with fatty foods

.. Contact with acidic foods

USA STANDARDS



ANSI-ISEA 105:2016 Hand protection

A3: Resistance to cutting by sharp objects (from A1 to A9)

References

References	Bar code	COLOUR	SIZE		
VECUT5507	00	Yellow-Grey	07	120	12
VECUT5509	00	Yellow-Grey	09	120	12
VECUT5510	00	Yellow-Grey	10	120	12