

# EASYSEAL EZ 100

## ACRYLIC SEALANT

### DESCRIPTION

**EASYSEAL EZ 100** is a specially formulated water based, acrylic sealer for both indoor and outdoor use. It is a non-flammable product that provides permanent flexibility and has excellent water resistance and sealing characteristics.

### APPLICATIONS

**EASYSEAL EZ 100** is used as a sealer for indoor and outdoor use and also is suitable for low to high pressure metal air distribution systems and Duct application.

### ADVANTAGES

- Non-Flammable
- Permanently flexible
- Excellent water resistance
- Non-Staining
- Paintable
- Mold and mildew resistance.
- Soundproof.

### TECHNICAL SPECIFICATION

Physical Properties	Test Method	Typical Value
Specific gravity		1.67
Flow (sag or slump)	ASTM C-639-01	Non sag
Skin Forming time		2-5 minutes
Tack free time	ASTM C-679-87	20 minutes
Tensile strength, (N/mm <sup>2</sup> )	ASTM D-412-98a	1.1
Elongation,%	ASTM D-412-98a	>140
Application Temperature		+5°C to +50°C

### IMPORTANT INFORMATION

**EASYSEAL EZ 100** is not recommended to be used where high movement accommodation is needed. It is also not suited to use on oily or bituminous substrates, rubber or building material that may bleed oils.

## COLOURS

**EASYSEAL EZ 100** is available in grey, cream and white. Other colors are available upon request.

## PACKAGING

300ml cartridge, 400ml sausage and 600ml sausage. 4 kg Bucket and 200 Ltr Drum.

## SAFETY

Safety data sheet available upon request.

## STORAGE AND SHELF LIFE

EASYSEAL EZ 100 acrylic sealant has a shelf life of 12 months if stored in a cool (below 25°C), dry place in its original moisture-tight container. However, if the material is kept beyond the recommended shelf life, it is not necessarily unusable, but a check should be performed to observe whether the product is still workable, applicable and uncured. **KEEP FROM FREEZING.**

### Note:

*All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control. Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields. Information on this datasheet is subject to change without notice and should not be used for writing specification. For additional information on specific applications, please contact Triton Middle East, LLC. The information contained herein, particularly recommendations for the handling and use of our products, is based on our professional experience. As materials and conditions may vary with each intended application, and thus are beyond our sphere of influence, we strongly recommend that in each case sufficient tests are conducted to check the suitability of our products for their intended use. Legal liability cannot be accepted on the basis of the contents of this data sheet or any verbal advice given, unless there is a case of wilful misconduct or gross negligence on our part. This technical data sheet super sedes all previous editions relevant to this product. Triton reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.*

Product of:

