



Safety Data Sheet Regulation EC No 1907/2006 Art.31

Productname : Galva Brite Creationdate : 09.06.20 Version : 4.0
Ref.Nr.: BDS002119_3_20200609 (EN) Replaces: BDS002119_20200504

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Galva Brite
Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Anti Corrosion Products

1.3. Details of the supplier of the safety data sheet

CRC Industries Europe BV
Touwslagerstraat 1
9240 Zele
Belgium
Tel.: +32(0)52/45.60.11
Fax.: +32(0)52/45.00.34
E-mail : hse@crcind.com

Subsidiaries		Tel	Fax
CRC Industries Finland Oy	Smedsgatan 3-5 LT4, PL62, 08101 LOJO	+358/(19)32.921	
CRC Industries France	6, avenue du marais, C.S. 90028, 95102 Argenteuil Cedex	01.34.11.20.00	01.34.11.09.96
CRC Industries Deutschland GmbH	Südring 9, D-76473 Iffezheim	(07229) 303 0	(07229)30 32 66
CRC INDUSTRIES IBERIA S.L.U.	GREMIO DEL CUERO-PARC.96, POLIGONO INDUSTRI. DE HONTORIA, 40195 SEGOVIA	0034/921.427.546	0034/921.436.270
CRC Industries Sweden	Laxfiskevägen 16, 433 38 Partille	0046/31 706 84 80	0046/31 27 39 91

1.4. Emergency telephone number

CRC Industries Europe, Belgium: Tel.: +32(0)52/45.60.11 (office hours)

Safety Data Sheet Regulation EC No 1907/2006 Art.31

Productname : Galva Brite **Creationdate :** 09.06.20 Version : 4.0
Ref.Nr.: BDS002119_3_20200609 (EN) **Replaces:** BDS002119_20200504

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Physical: Aerosols, category 1
Extremely flammable aerosol.
Pressurised container: May burst if heated.
Classification is based on test data.

Health: Specific target organ toxicity - single exposure, category 3
May cause drowsiness or dizziness.
Specific Target Organ Toxicity - Repeated Exposure Category 2
May cause damage to organs through prolonged or repeated exposure .
Classification based on calculation method.

Environment: Hazardous to the aquatic environment, chronic category 3
Harmful to aquatic life with long lasting effects.
Classification based on calculation method.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008

Product identifier: Contains:
Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclic

Hazard pictogram(s):



Signal word: Danger

Hazard statement(s): H222 : Extremely flammable aerosol.
H229 : Pressurised container: May burst if heated.
H336 : May cause drowsiness or dizziness.
H373 : May cause damage to organs through prolonged or repeated exposure

H412 : Harmful to aquatic life with long lasting effects.

Precautionary statement(s): P102 : Keep out of reach of children.
P210 : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 : Do not spray on an open flame or other ignition source.
P251 : Do not pierce or burn, even after use.
P261-1 : Avoid breathing vapours/spray.
P271 : Use only outdoors or in a well-ventilated area.
P410/412 : Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501-2 : Dispose of contents/container to an authorised waste collection point.

**Supplemental Hazard**

None

information:

Dir. 2004/42/EC on the limitation of emissions of volatile organic compounds (VOC) of organic solvents in certain paints and Cat.II B(e) VOC max 840 g/L < 675 g/L varnishes and vehicle refinishing products

2.3. Other hazards

No information available

SECTION 3: Composition/information on ingredients**3.1. Substances**

Not applicable.

Safety Data Sheet Regulation EC No 1907/2006 Art.31

Productname : Galva Brite **Creationdate :** 09.06.20 Version : 4.0
Ref.Nr.: BDS002119_3_20200609 (EN) **Replaces:** BDS002119_20200504

3.2. Mixtures

Hazardous ingredient	Registration number	CAS-nr.	EC-nr	w/w %	Hazard Class and Category	Hazard statement	Notes
dimethyl ether	01-2119472128-37	115-106	204-065-8	50-75	Flam. Gas 1, Press. Gas	H220,H280	A
ethyl acetate	01-2119475103-46	141-786	205-500-4	5-10	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3	H225,H319,H336	B
Hydrocarbons, C9-12, nalkanes, isoalkanes, cyclic	01-2119458049-33	64742-82-1	(919-446-0)	5-10	Flam. Liq. 3, Asp. Tox. 1, STOT SE 3, STOT RE 1, Aquatic Chronic 2	H226,H304,H336,H372,H411	B,Q
n-butyl acetate	01-2119485493-29	123-864	204-658-1	1-5	Flam. Liq. 3, STOT SE 3	H226,H336	
Hydrocarbons, C9, aromatics	01-2119455851-35	-	(918-668-5)	<2.5	Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2	H226,H335,H336,H304,H411	Q
Hydrocarbons, C9-C11, nalkanes, isoalkanes, cyclics, < 2% aromatics	01-2119463258-33	-	(919-857-5)	<2.5	Flam. Liq. 3, Asp. Tox. 1, STOT SE 3	H226,H304,H336	B,Q
zinc oxide	01-2119463881-32	1314-13-2	215-222-5	<1.1	Aquatic Acute 1, Aquatic Chronic 1	H400,H410	B

Safety Data Sheet Regulation EC No 1907/2006 Art.31

Productname : Galva Brite **Creationdate :** 09.06.20 Version : 4.0
Ref.Nr.: BDS002119_3_20200609 (EN) **Replaces:** BDS002119_20200504

2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime	01-2119539477-28	96-29-7	202-496-6	<0.1	Carc. 2, Acute Tox. 4, Eye Dam. 1, Skin Sens. 1	H351,H312,H318,H317	B
--	------------------	---------	-----------	------	---	---------------------	---

Explanation notes

A : substance with Community workplace exposure limit

B : substance with national established workplace exposure limit

Q : The CAS-no is only an indicative identifier to be used outside the EU for global inventory entries.

(* Explanation phrases : see chapter 16)

SECTION 4: First aid measures

4.1. Description of first aid measures

Contact with eyes : If substance has got into eyes, immediately wash out with plenty of water
If eye irritation persists: Get medical advice/attention.

Contact with skin : Wash with plenty of soap and water.
If skin irritation occurs: Get medical advice/attention.

Inhalation : IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER or doctor/physician if you feel unwell.

Ingestion : If swallowed do not induce vomiting because of risk of aspiration into the lungs.
If aspiration is suspected obtain immediate medical attention

4.2. Most important symptoms and effects, both acute and delayed

Inhalation : Excessive inhalation of solvent vapours may give rise to nausea, headaches and dizziness

Ingestion : After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia.

Symptoms : sore throat, abdominal pain, nausea, vomiting

Skin contact : May cause irritation.

Symptoms : redness and pain

Eye contact : May cause irritation.

Symptoms : redness and pain

4.3. Indication of any immediate medical attention and special treatment needed

General Advice : If you feel unwell, seek medical advice (show the label where possible)
If symptoms persist always call a doctor

SECTION 5: Firefighting measures

5.1. Extinguishing media



foam, carbon dioxide or dry agent

Do not use water jet extinguishing media, due to the risk of spreading fire.

5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C

Forms hazardous decomposition products

CO,CO₂

5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water

In case of fire, do not breathe fumes

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources

Ensure adequate ventilation

Wear suitable protective clothing and gloves.

In case of insufficient ventilation, wear suitable respiratory equipment.

6.2. Environmental precautions

Do not allow to enter public sewers and watercourses

If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities

6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material

6.4. Reference to other sections

For further information see section 8

Safety Data Sheet Regulation EC No 1907/2006 Art.31

Productname :	Galva Brite	Creationdate :	09.06.20 Version : 4.0
Ref.Nr.:	BDS002119_3_20200609 (EN)	Replaces:	BDS002119_20200504

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Safety Data Sheet Regulation EC No 1907/2006 Art.31

Productname : Galva Brite **Creationdate :** 09.06.20 Version : 4.0
Ref.Nr.: BDS002119_3_20200609 (EN) **Replaces:** BDS002119_20200504

Keep away from heat and sources of ignition
Take precautionary measures against static discharge
Equipment should be earthed
Use explosion-proof electrical/ventilating/lighting/.../equipment.
Use only non-sparking tools.
Do not breathe aerosols or vapours.
Ensure adequate ventilation
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid contact with skin and eyes.
Wash thoroughly after use
Wear protective gloves/protective clothing/eye protection/face protection.

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C.
Keep out of reach of children.

7.3. Specific end use(s)

Anti Corrosion Products

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits :

Hazardous ingredient	CAS-nr.	method	
EU established exposure limits:			
dimethyl ether	115-10-6	TWA	1000 ppm
ethyl acetate	141-78-6	TWA	200 ppm
		STEL	400 ppm
National established exposure limits, United Kingdom			
dimethyl ether	115-10-6	TWA	400 ppm
		STEL	500 ppm
n-butyl acetate	123-86-4	TWA	150 ppm
		STEL	200 ppm
ethyl acetate	141-78-6	TWA	200 ppm

		STEL	400 ppm
National established exposure limits, Ireland			
dimethyl ether	115-10-6	TWA	1000 ppm
		STEL	-
n-butyl acetate	123-86-4	TWA	150 ppm
		STEL	200 ppm
ethyl acetate	141-78-6	TWA	200 ppm
		STEL	400 ppm
2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime	96-29-7	TWA	3 ppm
		STEL	10 ppm

8.2. Exposure controls

Control procedures :	Ensure adequate ventilation Keep away from heat and sources of ignition Take precautionary measures against static discharges
Personal protection :	Take precautions to avoid contact with skin and eyes when handling the product. It is good practice to wear gloves and to provide adequate ventilation whenever using the product. In all cases handle and use the product in accordance with good industrial hygiene practices.
inhalation :	In case of insufficient ventilation, wear suitable respiratory equipment.
recommended respiratory protection:	Air purifying respirator equipped with organic gas/vapor cartridge (type A)
hands and skin :	Depending on amount and duration of use and the risk of contact with the product the gloves manufacturer can assist you in the selection of the right glove material and breakthrough time.
Recommended gloves:	Nitrile
eyes :	Wear safety eyewear according to EN 166.
Environmental protection:	Avoid release to the environment. Collect spillage.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

(for aerosols data for the product without propellant)

Appearance : physical state :	DME propelled liquid.
colour :	Grey.
odour :	Solvent.
pH :	Not applicable.
Boiling point/range :	Not available.
Flash point :	< 0 °C
Evaporation rate :	Not available.
Explosion limits : upper limit:	Not available.
lower limit :	Not available.
Vapour pressure :	Not available.
Relative density :	0.969 g/cm ³ (@ 20°C).
Solubility in water :	Insoluble in water
Auto-ignition :	> 200 °C
Viscosity :	Not applicable.

9.2. Other information

Safety Data Sheet Regulation EC No 1907/2006 Art.31

Productname : Galva Brite **Creationdate :** 09.06.20 **Version :** 4.0
Ref.Nr.: BDS002119_3_20200609 (EN) **Replaces:** BDS002119_20200504

Productname : Galva Brite Creationdate : 09.06.20 Version : 4.0

Ref.Nr.: BDS002119_3_20200609 (EN) Replaces: BDS002119_20200504

VOC = volatile organic < 675 g/l compounds

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reactions known if used for its intended purpose

10.2. Chemical stability

10.3. Possibility of hazardous reactions

Stable

No hazardous reactions known if used for its intended purpose

10.4. Conditions to avoid

Avoid overheating

10.5. Incompatible materials

Strong oxidising agent

10.6. Hazardous decomposition products

CO,CO2

SECTION 11: Toxicological information

11.1. Information on toxicological effects

acute toxicity: based on available data the classification criteria are not met **skin**

corrosion/irritation: based on available data the classification criteria are not met **serious**

eye damage/irritation: based on available data the classification criteria are not met **respiratory**
or skin

sensitisation: based on available data the classification criteria are not met **germ cell**

mutagenicity: based on available data the classification criteria are not met **carcinogenicity:**

based on available data the classification criteria are not met **toxicity for reproduction:** based

on available data the classification criteria are not met **STOT-single exposure:** May cause
drowsiness or dizziness.

STOT repeated exposure: May cause damage to organs through prolonged or repeated exposure .

aspiration hazard: based on available data the classification criteria are not met

Productname : Galva Brite Creationdate : 09.06.20 Version : 4.0

Ref.Nr.: BDS002119_3_20200609 (EN) Replaces: BDS002119_20200504

Information on likely routes of exposure:

Inhalation : Inhalation of solvent vapours may give rise to nausea, headaches and dizziness
 After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia.

Ingestion :

Skin contact : Prolonged skin contact will result in defatting of the skin, leading to irritation, and in some cases, dermatitis

Eye contact : Repeated exposure may cause skin dryness or cracking.

Hazardous ingredient	CAS-nr.	method	
dimethyl ether	115-10-6	LC50 inhal.rat	309 mg/l
n-butyl acetate	123-86-4	LD50 oral rat	10760 mg/kg
		LC50 inhal.rat	> 20 mg/l
		LD50 derm.rabit	> 1400 mg/kg
zinc oxide	1314-13-2	LD50 oral rat	7950 mg/kg
		LC50 inhal.rat	> 5.7 mg/l
ethyl acetate	141-78-6	LD50 oral rat	5620 mg/kg
		LC50 inhal.rat	30 mg/l
		LD50 derm.rabit	> 20000 mg/kg
2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime	96-29-7	LD50 oral rat	2326 mg/kg
		LD50 derm.rabit	1000 mg/kg
Hydrocarbons, C9, aromatics	-	LD50 oral rat	3492 mg/kg
		LC50 inhal.rat	> 6.393 mg/l
		LD50 derm.rabit	> 3160 mg/kg
Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclic	64742-82-1	LD50 oral rat	> 5000 mg/kg
		LC50 inhal.rat	> 10 mg/l
		LD50 derm.rabit	> 4 mg/kg
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	-	LD50 oral rat	>5000 mg/kg
		LC50 inhal.rat	4951 mg/m3
		LD50 derm.rabit	>5000 mg/kg

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, chronic category 3
 May cause irritation.

Toxicological data :

Harmful to aquatic life with long lasting effects.

Ecotoxicological data:

Productname : Galva Brite **Creationdate :** 09.06.20 Version : 4.0

Ref.Nr.: BDS002119_3_20200609 (EN) **Replaces:** BDS002119_20200504

		LC50 fish	18 mg/l
		EC50 daphnia	44 mg/l
zinc oxide	1314-13-2	IC50 algae	0.136 mg/l
		LC50 fish	0.169 mg/l
		EC50 daphnia	1.7 mg/l
ethyl acetate	141-78-6	IC50 algae	5600 mg/l
		LC50 fish	230 mg/l
		EC50 daphnia	610 mg/l
2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime	96-29-7	IC50 algae	11.8 mg/l
		LC50 fish	> 100 mg/l
		EC50 daphnia	201 mg/l
Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclic	64742-82-1	IC50 algae	4.6-10 mg/l
		LC50 fish	10-30 mg/l
		EC50 daphnia	10-22 mg/l

12.2. Persistence and degradability

Hazardous ingredient	CAS-nr.	method	
dimethyl ether	115-10-6	IC50 algae	154.9 mg/l
		LC50 fish	4.1 mg/l
		EC50 daphnia	4.4 mg/l
n-butyl acetate	123-86-4	IC50 algae	647 mg/l

12.3. Bioaccumulative potential

No experimental data available

No experimental data available

12.4. Mobility in soil

Insoluble in water

Productname : Galva Brite **Creationdate :** 09.06.20 Version : 4.0

Ref.Nr.: BDS002119_3_20200609 (EN) **Replaces:** BDS002119_20200504

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

No experimental data available
GWP (global warming potential): 1

SECTION 13: Disposal considerations

13.1. Waste treatment methods

National regulations : Disposal should be in accordance with local, state or national legislation

SECTION 14: Transport information

14.1. UN number

UN-number : 1950
No information available

Safety Data Sheet Regulation EC No 1907/2006 Art.31

Proper shipping name: AEROSOLS

14.3. Transport hazard class(es)

Class: 2.1
ADR/RID - Classification code: 5F
ADR/RID - Environmentally hazardous: No
IMDG - Marine pollutant: No
IATA/ICAO - Environmentally hazardous: No

14.6. Special precautions for user

ADR/RID - Tunnelcode: (D)
IMDG - Ems: F-D, S-U
IATA/ICAO - PAX: 203
IATA/ICAO - CAO: 203

Productname : Galva Brite

Creationdate : 09.06.20 Version : 4.0

Ref.Nr.: BDS002119_3_20200609 (EN)

Replaces: BDS002119_20200504

14.2. UN proper shipping name

14.4. Packing group

Packing group: Not applicable.

14.5. Environmental hazards

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements.
Dir. 2013/10/EU, 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC.
Regulation (EC) No 1907/2006 (REACH)
EU-directive 99/45/EC
Regulation (EC) No 1272/2008 (CLP)

15.2. Chemical safety assessment

No information available

SECTION 16: Other information

Safety Data Sheet Regulation EC No 1907/2006 Art.31

Productname : Galva Brite **Creationdate :** 09.06.20 Version : 4.0
Ref.Nr.: BDS002119_3_20200609 (EN) **Replaces:** BDS002119_20200504

*Explanation hazard statements: H220 : Extremely flammable gas.
H225 : Highly flammable liquid and vapour.
H226 : Flammable liquid and vapour.
H280 : Contains gas under pressure; may explode if heated.
H304 : May be fatal if swallowed and enters airways.
H312 : Harmful in contact with skin.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H335 : May cause respiratory irritation.
H336 : May cause drowsiness or dizziness.
H351 : Suspected of causing cancer .
H372 : Causes damage to organs through prolonged or repeated exposure.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.
H411 : Toxic to aquatic life with long lasting effects.

REVISIONS IN CHAPTRE : Labelling according to Regulation (EC) No 1272/2008

acronyms and synonyms: TWA = time weight average
 STEL = short time exposure limit
 VOC = volatile organic compounds
 PBT = persistant bioaccumulative toxic
 vPvB = very persitant very bioaccumulative

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties.

Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.