

Window adhesive Classic Plus

Elastic 1-component window adhesive with excellent stability

High-modulus

For all popular vehicle types in passenger vehicle, commercial vehicle, bus, truck, agricultural and construction machine sectors

Antenna compatible, non-conductive

Prevents contact corrosion

Suitable for use on aluminium-magnesium and hybrid bodywork (e. g. Audi A8, Jaguar XJ etc.)

Tested safety

- Drive-away time confirmed with crash test and TÜV certificate in accordance with FMVSS208/212!
- Meets requirements of original equipment manufacturers (vehicle manufacturers)



Chemical basis	Moisture curing 1K polyurethane
Max. open time/conditions	15 min/at 23 °C and 50% humidity
Min./max. processing temperature	5 to 35 °C
Shelf life from production/conditions	12 Month/at 5 °C to 25 °C

Contents	Container	Art. no.	P. Qty.
310 ml	Cartridge	0890 023 701	1/12
400 ml	Bag	0890 023 711	15

Details/Application

Can be used for all standard vehicle types in the passenger car, commercial vehicle, bus, van and agricultural and construction machinery sectors



Instructions

When applying the material, ensure that the working environment is clean. It is essential to use the product with the accompanying Würth system components to ensure correct and faultless work. The work instructions provided with the product must be followed during application.

A Varioprimer must be applied to freshly-painted surfaces. Before applying the primer, the paint must be allowed to harden completely.

Notice

It is imperative that the Würth active cleaner and Würth Varioprimer are used when preparing surfaces. The products must be checked to ensure that they have not expired before they are used. Apply the adhesive while guiding the gun vertically, starting from the centre at the bottom of the window. Do not position the vehicle on the lifting platform. Observe the information regarding bead geometry provided by the vehicle manufacturer. The application and drive-away times must be observed.

The usage instructions are recommendations based on the tests we have conducted and are based on our experience; carry out your own tests before each application. Due to the large number of applications and storage and processing conditions, we do not assume any liability for a specific application result. Insofar as our free customer service provides technical information or acts as an advisory service, no responsibility is assumed by this service except where the advice or information given falls within the scope of our specified, contractually agreed service or the advisor was acting deliberately. We guarantee consistent quality of our products. We reserve the right to make technical changes and carry out further development.

Related products for	Designation	Art. no.
0890 023 701	Varioprimer safe + easy	0890 024 010
	Varioprimer safe + easy	0890 024 021
	Glass cleaner Active cleaner	0890 024 1
	Varioprimer safe + easy	0890 024 101
	Window application nozzle	0891 023 001
	Primer brush	0891 650
	Standard window application nozzle	0891 651
	Basic cleaner S	0890 024 6
	Windscreen lining tape	0891 655
0890 023 711	Varioprimer safe + easy	0890 024 010
	Varioprimer safe + easy	0890 024 021
	Glass cleaner Active cleaner	0890 024 1
	Varioprimer safe + easy	0890 024 101
	Window application nozzle	0891 023 001
	Primer brush	0891 650
	Standard window application nozzle	0891 651 0
	Adapters	0891 651 10
	Basic cleaner S	0890 024 6
Windscreen lining tape	0891 655	