Safety Data Sheet

KERAFLEX MAXI S1 (N) GREY

Safety Data Sheet dated: 29/12/2020 - version 1

Date of first edition: 29/12/2020



1: Identification

GHS Product Identifier

Mixture identification:

Trade name: KERAFLEX MAXI S1 (N) GREY

Trade code: 9012030

Recommended use of the chemical and restrictions on use

Recommended use: Cement based powder adhesive

Uses advised against: Data not available

Supplier's details



2: Hazard identification

Classification of the substance or mixture

Skin Irrit. 2 Causes skin irritation.

Eye Dam. 1 Causes serious eye damage.

Skin Sens. 1B May cause an allergic skin reaction. STOT SE 3 May cause respiratory irritation.

Adverse physicochemical, human health and environmental effects:

No other hazards

GHS label elements, including precautionary statements

Pictograms and Signal Words



Hazard statements:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.H335 May cause respiratory irritation.

Precautionary statements:

P261 Avoid breathing dust.

P264 Wash hands thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...

P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P312 Call a POISON CENTER if you feel unwell.

P321 Specific treatment (see supplementary instructions on this label)

P333+P313 If skin irritation or rash occurs: Get medical advice.

P362+P364 Take off contaminated clothing and wash it before reuse.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with applicable regulations.

Print date 29/03/2022 Production Name KERAFLEX MAXI S1 (N) GREY Page n. 1 of 6

Other hazards which do not result in a classification

No other hazards

Prolonged exposition and/or intensive inhalation of respirable free crystalline silica (average diameter less than 10 micron in accordance with ACGIH) can cause pulmonary fibrosis commonly referred to as silicosis.

This preparation contains cement. Contact between cement and body fluids (e.g. sweat and eye fluids) may cause irritation or burns

3: Composition/information on ingredients

Substances

Not available

Mixtures

Hazardous components within the meaning of GHS and related classification:

Concentration (% w/w)	Name	Ident. Numb.	Classification	Registration Number
≥25 - <50 %	portland cement, Cr(VI) < 2 ppm		Skin Irrit. 2, H315; Skin Sens. 1B, H317; Eye Dam. 1, H318; STOT SE 3, H335	

4: First-aid measures

Description of necessary first-aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

In case of inhalation, consult a doctor immediately and show him packing or label.

Most important symptoms/effects, acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

Indication of immediate medical attention and special treatment needed, if necessary

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

5: Fire-fighting measures

Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Unsuitable extinguishing media:

None in particular.

Special hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: Not available

Explosive properties: ==

Oxidizing properties: Not available

Special protective actions for fire-fighters

Use suitable breathing apparatus.

 $\hbox{Collect contaminated fire extinguishing water separately. This must not be discharged into drains. } \\$

Move undamaged containers from immediate hazard area if it can be done safely.

Print date 29/03/2022 Production Name KERAFLEX MAXI S1 (N) GREY Page n. 2 of 6

6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Methods and material for containment and cleaning up

Take up mechanically and dispose of according to local/state/federal regulations

Scoop into containers and seal for disposal.

Retain contaminated washing water and dispose it.

7: Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Do not use on extensive surface areas in premises where there are occupants.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Keep away from food, drink and feed.

Incompatible materials:

Print date

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

8: Exposure controls/personal protection Control parameters

29/03/2022

Production Name

List of components with OEL value

List of components with OEL value										
	Component	OEL Type	Country	Ceiling	Long Term mg/m3	Long Term ppm	Short Term mg/m3	Short Term ppm	Behaviour	Note
	portland cement, Cr(VI) < 2 ppm	IDN	INDONESIA		10					5 mg/m3 TWA (containing <1% of free Silica, respirable dust);10 mg/m3 TWA (containing <1% of free Silica, total dust)
		ZAF	SOUTH AFRICA		10					
		ARE	UNITED ARAB EMIRATES		10					A4 - Not Classifiable as a Human Carcinogen; pulmonary function; respiratory symptoms; asthma
		PAN	PANAMA		5.000		30			
		IDN	INDONESIA		10					10 mg/m3 PEL
		MEX	MEXICO		1					
		IND	INDIA		10					
		IDN	INDONESIA		10					
		ZAF	SOUTH AFRICA		5					
		COL	COLOMBIA		1					
		PER	PERU		10					
		ARE	UNITED ARAB EMIRATES		10					
		PAN	PANAMA		10		10			
		PAN	PANAMA		5		10			

KERAFLEX MAXI S1 (N) GREY

Page n.

3 of 6

PAN PANAMA 10 20

Appropriate engineering controls: Not available

Individual protection measures, such as personal protective equipment (PPE)

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use respiratory protection where ventilation is insufficient or exposure is prolonged.

9: Physical and chemical properties

Color: Grey

Appearance: powder Odour: cement like

Odour threshold: Not available

pH: Not available

pH (water dispersion, 10%): 12.00

Melting point / freezing point: Not available
Initial boiling point and boiling range: Not available

Flash point: Not available Evaporation rate: Not available Solid/gas flammability: Not available

Upper/lower flammability or explosive limits: Not available

Vapour pressure: Not available Vapour density: Not available Relative density: Not available Solubility in water: partly soluble

Solubility in oil: Insoluble

Partition coefficient (n-octanol/water): Not available

Auto-ignition temperature: Not available Decomposition temperature: Not available

Viscosity: Not available

10: Stability and reactivity

Reactivity

Stable under normal conditions

Chemical stability

Data not available.

Possibility of hazardous reactions

None.

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

Hazardous decomposition products

11: Toxicological information

Information on toxicological effects

Toxicological information of the product: No data available

12: Ecological information

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

No data available

Persistence and degradability

Print date 29/03/2022 Production Name KERAFLEX MAXI S1 (N) GREY Page n. 4 of 6

Not available

Bioaccumulative potential

Not available

Mobility in soil

Not available

Other adverse effects

No Components with evironmental hazard properties found.

13: Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

14: Transport information

Not classified as dangerous in the meaning of transport regulations.

UN number

Not available

UN proper shipping name

Not available

Transport hazard class(es)

Not available

Packing group, if applicable

Road and Rail (ADR-RID) :

Not available

Air (IATA):

Not available

Sea (IMDG):

Not available

Environmental hazards

Marine pollutant: No

Environmental Pollutant: Not available

Special precautions for user

Not available

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not available

15: Regulatory information

Safety, health and environmental regulations specific for the product in question

This Safety Data Sheet has been prepared according to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS), Fifth revised edition.

SCAQMD Rule 1113 : N.A. SCAQMD Rule 1168: N.A.

Print date 29/03/2022 Production Name KERAFLEX MAXI S1 (N) GREY Page n. 5 of 6

16: Other information

Code	Description
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

Insert here further consulted bibliography

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity. WGK: German Water Hazard Class.

KSt: Explosion coefficient.

Print date 29/03/2022 Production Name KERAFLEX MAXI S1 (N) GREY Page n. 6 of 6