### Conex | Bänninger

# Delcop End Feed


A range of copper capillary soldering and brazing fittings.



#### **Features and Benefits:**

- Available in sizes 6-54mm.
- Suitable for connecting copper tubes in accordance with EN 1057.
- Designed for soldering and brazing application with the exception of union fittings with copper tail, which cannot be brazed.
- Manufactured with copper and gunmetal which are immune to dezincification.

Conex Delcop End Feed fittings (Silver brazing)			
Size (mm)	Working Pressure (bar)		
	-20° to 110°C	150°C	200°C
6	79.1	67.3	35.6
8	57.9	49.2	26.1
10	45.7	38.8	20.5
12	37.7	32.0	17.0
15	35.1	29.8	15.8
18	33.3	28.3	15.0
22	30.6	26.0	13.8
28	23.8	20.3	10.7
35	21.1	17.9	9.5
42	19.3	16.4	8.7
54	16.3	13.9	7.3



#### Conex | Bänninger

## **Delcop End Feed**

#### Delcop Endfeed Range



From:





From:



From:



From: 54 x 42mm



From:



From: 15 x 10mm











Size: 15mm



From: 22 x 1"













DC816



From: 35 x 3/4" To: 54 1.1/2"



DC607 From: 6mm To: 54mm



From:



From: 10mm



Male Straight Connector







From: To:



From:



From: 28 x1" To: 28 x1"



From: To:











15 x 1/2" 22 x3/4"



15 x 1/2" 35 x1.1/4"



From:



15 x15 x10mm 54 x 54 x 42mm From: To:



Size: 22mm

22 x 15 x 22mm 42 x 28 x 42mm









Size: 35 x 15 x 35mm



From:



DC712 From:



DC714 From:



From:











