

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-PE 510 - 585 ML (Comp. B)

Version	Revision Date:	SDS Number:	Date of last issue: 09.06.2022
2.3	11.07.2022	8236679-00006	Date of first issue: 13.04.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	:	WIT-PE 510 - 585 ML (Comp. B)
Product code	:	5916615585
Unique Formula Identifier (UFI)	:	2YA3-30MU-4009-WW4D

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture	:	Professional use product Construction material, Dual-component adhesive
Recommended restrictions on use	:	Not applicable

1.3 Details of the supplier of the safety data sheet

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4	H302: Harmful if swallowed.
Skin corrosion, Sub-category 1A	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-PE 510 - 585 ML (Comp. B)

Version 2.3 Revision Date: 11.07.2022 SDS Number: 8236679-00006 Date of last issue: 09.06.2022
Date of first issue: 13.04.2021

Hazard pictograms :



Signal word : Danger

Hazard statements : H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.

Precautionary statements : **Prevention:**
P260 Do not breathe dust or mist.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P330 + P331 + P310 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353 + P310 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Immediately call a POISON CENTER/ doctor.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

Hazardous components which must be listed on the label:

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine
m-phenylenebis(methylamine)
2,4,6-Tris{(Dimethylamino)methyl}phenol
p-Toluenesulphonic acid (containing a maximum of 5 % H₂SO₄)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-PE 510 - 585 ML (Comp. B)

Version 2.3 Revision Date: 11.07.2022 SDS Number: 8236679-00006 Date of last issue: 09.06.2022
Date of first issue: 13.04.2021

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Amines

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine	25513-64-8 247-063-2 01-2119560598-25	Acute Tox. 4; H302 Skin Corr. 1A; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 EUH071 Acute toxicity estimate Acute oral toxicity: 910 mg/kg	>= 30 - < 50
m-phenylenebis(methylamine)	1477-55-0 216-032-5 01-2119480150-50	Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1B; H317 Aquatic Chronic 3; H412 EUH071 Acute toxicity estimate Acute inhalation toxicity (dust/mist): 1,34 mg/l	>= 5 - < 10
2,4,6-Tris{(Dimethylamino)methyl}phenol	90-72-2 202-013-9 603-069-00-0 01-2119560597-27	Acute Tox. 4; H302 Skin Corr. 1C; H314 Eye Dam. 1; H318 EUH071 Acute toxicity estimate Acute oral toxicity: 1.653 mg/kg	>= 5 - < 10
p-Toluenesulphonic acid (containing a maximum of 5 % H2SO4)	104-15-4 203-180-0 016-030-00-2 01-2119538811-39	Acute Tox. 4; H302 Skin Corr. 1C; H314 Eye Dam. 1; H318 EUH071	>= 3 - < 5

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-PE 510 - 585 ML (Comp. B)

Version 2.3 Revision Date: 11.07.2022 SDS Number: 8236679-00006 Date of last issue: 09.06.2022
Date of first issue: 13.04.2021

		specific concentration limit STOT SE 3; H335 >= 20 %	
		Acute toxicity estimate Acute oral toxicity: 1.410 mg/kg	
Quartz (SiO ₂)	14808-60-7 238-878-4	STOT RE 1; H372 (Lungs)	>= 1 - < 10

For explanation of abbreviations see section 16.

Alternative CAS Numbers for some regions

Chemical name	Alternative CAS Number(s)
2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine	25513-64-8

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- If inhaled : If inhaled, remove to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
Get medical attention immediately.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention immediately.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention immediately.
- If swallowed : If swallowed, DO NOT induce vomiting.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-PE 510 - 585 ML (Comp. B)

Version	Revision Date:	SDS Number:	Date of last issue: 09.06.2022
2.3	11.07.2022	8236679-00006	Date of first issue: 13.04.2021

If vomiting occurs have person lean forward.
Call a physician or poison control centre immediately.
Rinse mouth thoroughly with water.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Harmful if swallowed.
May cause an allergic skin reaction.
Causes serious eye damage.
Causes severe burns.

Causes digestive tract burns.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides
Nitrogen oxides (NO_x)
Sulphur oxides
Silicon oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-PE 510 - 585 ML (Comp. B)

Version	Revision Date:	SDS Number:	Date of last issue: 09.06.2022
2.3	11.07.2022	8236679-00006	Date of first issue: 13.04.2021

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.
Avoid breathing dust, fume, gas, mist, vapours or spray.
Do not breathe dust or mist.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-PE 510 - 585 ML (Comp. B)

Version 2.3 Revision Date: 11.07.2022 SDS Number: 8236679-00006 Date of last issue: 09.06.2022
Date of first issue: 13.04.2021

Do not eat, drink or smoke when using this product.
Take care to prevent spills, waste and minimize release to the environment.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep in properly labelled containers. Store locked up. Keep tightly closed. Store in accordance with the particular national regulations.

Advice on common storage : Do not store with the following product types:
Strong oxidizing agents
Self-reactive substances and mixtures
Organic peroxides
Explosives

Storage class (TRGS 510) : 8A

Recommended storage temperature : 5 - 35 °C

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Silicon, amorphous	112945-52-5	AGW (Inhalable fraction)	4 mg/m ³ (Silica)	DE TRGS 900
Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				
Quartz (SiO ₂)	14808-60-7	TWA (Respirable dust)	0,1 mg/m ³	2004/37/EC
Further information: Carcinogens or mutagens				

These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Quartz (SiO₂)

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-PE 510 - 585 ML (Comp. B)

Version
2.3

Revision Date:
11.07.2022

SDS Number:
8236679-00006

Date of last issue: 09.06.2022
Date of first issue: 13.04.2021

Substance name	End Use	Exposure routes	Potential health effects	Value
m-phenylenebis(methylamine)	Workers	Inhalation	Long-term systemic effects	1,2 mg/m ³
	Workers	Inhalation	Long-term local effects	0,2 mg/m ³
	Workers	Skin contact	Long-term systemic effects	0,33 mg/kg bw/day
2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine	Consumers	Ingestion	Long-term systemic effects	0,05 mg/kg bw/day
p-Toluenesulphonic acid (containing a maximum of 5 % H ₂ SO ₄)	Workers	Inhalation	Long-term systemic effects	53,6 mg/m ³
	Workers	Skin contact	Long-term systemic effects	7,6 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	8,7 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	2,5 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	2,5 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2,4,6-Tris((Dimethylamino)methyl)phenol	Fresh water	0,084 mg/l
	Marine water	0,0084 mg/l
	Sewage treatment plant	0,2 mg/l
	Intermittent use/release	0,84 mg/l
m-phenylenebis(methylamine)	Fresh water	0,094 mg/l
	Marine sediment	0,0094 mg/l
	Intermittent use/release	0,152 mg/l
	Sewage treatment plant	10 mg/l
	Fresh water sediment	0,43 mg/kg
	Marine sediment	0,043 mg/kg
	Soil	0,045 mg/kg
2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine	Fresh water sediment	0,43 mg/kg
	Fresh water	0,102 mg/l
	Marine water	0,01 mg/l
	Freshwater - intermittent	0,315 mg/l
	Sewage treatment plant	72 mg/l
	Fresh water sediment	0,622 mg/kg dry weight (d.w.)
	Marine sediment	0,062 mg/kg dry weight (d.w.)
Soil	10 mg/kg dry weight (d.w.)	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-PE 510 - 585 ML (Comp. B)

Version 2.3 Revision Date: 11.07.2022 SDS Number: 8236679-00006 Date of last issue: 09.06.2022
Date of first issue: 13.04.2021

p-Toluenesulphonic acid (containing a maximum of 5 % H ₂ SO ₄)	Fresh water	0,073 mg/l
	Freshwater - intermittent	0,73 mg/l
	Marine water	0,0073 mg/l
	Sewage treatment plant	58 mg/l
	Fresh water sediment	0,0577 mg/kg dry weight (d.w.)
	Marine sediment	0,00577 mg/kg dry weight (d.w.)
	Soil	0,016 mg/kg dry weight (d.w.)

8.2 Exposure controls

Engineering measures

Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.

Personal protective equipment

Eye protection : Wear the following personal protective equipment:
Chemical resistant goggles must be worn.
If splashes are likely to occur, wear:
Face-shield
Equipment should conform to DIN EN 166

Hand protection

Material : Nitrile rubber
Break through time : > 480 min
Glove thickness : 0,7 mm
Directive : Equipment should conform to DIN EN 374

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
Equipment should conform to DIN EN 14387

Filter type : Combined particulates and organic vapour type (A-P)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-PE 510 - 585 ML (Comp. B)

Version	Revision Date:	SDS Number:	Date of last issue: 09.06.2022
2.3	11.07.2022	8236679-00006	Date of first issue: 13.04.2021

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	:	paste
Colour	:	grey red
Odour	:	characteristic
Odour Threshold	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flammability (solid, gas)	:	Not classified as a flammability hazard
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	Not applicable
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
pH	:	substance/mixture is non-soluble (in water)
Viscosity	:	
Viscosity, kinematic	:	Not applicable
Solubility(ies)	:	
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not applicable
Vapour pressure	:	Not applicable
Density	:	1,42 g/cm ³ (20 °C)
Relative vapour density	:	Not applicable
Particle characteristics	:	
Particle size	:	No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-PE 510 - 585 ML (Comp. B)

Version	Revision Date:	SDS Number:	Date of last issue: 09.06.2022
2.3	11.07.2022	8236679-00006	Date of first issue: 13.04.2021

9.2 Other information

Explosives	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Evaporation rate	:	Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Skin contact
Ingestion
Eye contact

Acute toxicity

Harmful if swallowed.

Product:

Acute oral toxicity	:	Acute toxicity estimate: 1.513 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Assessment: Not corrosive to the respiratory tract Acute toxicity estimate: > 5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-PE 510 - 585 ML (Comp. B)

Version 2.3 Revision Date: 11.07.2022 SDS Number: 8236679-00006 Date of last issue: 09.06.2022
Date of first issue: 13.04.2021

Components:

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine:

Acute oral toxicity : LD50 (Rat): 910 mg/kg
Acute toxicity estimate: 910 mg/kg
Method: Calculation method

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

m-phenylenebis(methylamine):

Acute oral toxicity : LD50 (Rat): > 200 - < 2.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 1,34 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: Corrosive to the respiratory tract.

Acute toxicity estimate: 1,34 mg/l
Test atmosphere: dust/mist
Method: Calculation method

Acute dermal toxicity : LD50 (Rat): > 3.100 mg/kg

2,4,6-Tris((Dimethylamino)methyl)phenol:

Acute oral toxicity : LD50 (Rat): 1.653 mg/kg
Acute toxicity estimate: 1.653 mg/kg
Method: Calculation method

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

p-Toluenesulphonic acid (containing a maximum of 5 % H₂SO₄):

Acute oral toxicity : LD50 (Rat): 1.410 mg/kg
Method: OECD Test Guideline 401
Acute toxicity estimate: 1.410 mg/kg
Method: Calculation method

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg
Remarks: Based on data from similar materials

Quartz (SiO₂):

Acute oral toxicity : LD50 (Rat): > 22.500 mg/kg

Skin corrosion/irritation

Causes severe burns.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-PE 510 - 585 ML (Comp. B)

Version 2.3 Revision Date: 11.07.2022 SDS Number: 8236679-00006 Date of last issue: 09.06.2022
Date of first issue: 13.04.2021

Components:

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Corrosive after 3 minutes or less of exposure

m-phenylenebis(methylamine):

Species : Rat
Result : Corrosive after 3 minutes to 1 hour of exposure

2,4,6-Tris((Dimethylamino)methyl)phenol:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Corrosive after 1 to 4 hours of exposure

p-Toluenesulphonic acid (containing a maximum of 5 % H₂SO₄):

Species : Rabbit
Method : OECD Test Guideline 404
Result : Corrosive after 1 to 4 hours of exposure

Quartz (SiO₂):

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Irreversible effects on the eye

m-phenylenebis(methylamine):

Result : Irreversible effects on the eye
Remarks : Based on skin corrosivity.

2,4,6-Tris((Dimethylamino)methyl)phenol:

Species : Rabbit
Result : Irreversible effects on the eye

p-Toluenesulphonic acid (containing a maximum of 5 % H₂SO₄):

Result : Irreversible effects on the eye
Remarks : Based on skin corrosivity.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-PE 510 - 585 ML (Comp. B)

Version 2.3 Revision Date: 11.07.2022 SDS Number: 8236679-00006 Date of last issue: 09.06.2022
Date of first issue: 13.04.2021

Quartz (SiO₂):

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation
Remarks : Based on data from similar materials

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Components:

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : positive

Assessment : Probability or evidence of high skin sensitisation rate in humans

m-phenylenebis(methylamine):

Test Type : Local lymph node assay (LLNA)
Exposure routes : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : positive

Assessment : Probability or evidence of low to moderate skin sensitisation rate in humans

2,4,6-Tris((Dimethylamino)methyl)phenol:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : equivocal

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative

p-Toluenesulphonic acid (containing a maximum of 5 % H₂SO₄):

Test Type : Maximisation Test

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-PE 510 - 585 ML (Comp. B)

Version	Revision Date:	SDS Number:	Date of last issue: 09.06.2022
2.3	11.07.2022	8236679-00006	Date of first issue: 13.04.2021

Exposure routes : Skin contact
Species : Guinea pig
Method : Regulation (EC) No. 440/2008, Annex, B.6
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)
Method: Directive 67/548/EEC, Annex, B.13/14
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Hamster
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 475
Result: negative

Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative

m-phenylenebis(methylamine):

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-PE 510 - 585 ML (Comp. B)

Version	Revision Date:	SDS Number:	Date of last issue: 09.06.2022
2.3	11.07.2022	8236679-00006	Date of first issue: 13.04.2021

Method: OECD Test Guideline 474
Result: negative

2,4,6-Tris((Dimethylamino)methyl)phenol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

p-Toluenesulphonic acid (containing a maximum of 5 % H₂SO₄):

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:

p-Toluenesulphonic acid (containing a maximum of 5 % H₂SO₄):

Species : Mouse
Application Route : Skin contact
Exposure time : 2 Years
Result : negative
Remarks : Based on data from similar materials

Reproductive toxicity

Not classified based on available information.

Components:

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 416
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rabbit
Application Route: Ingestion

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-PE 510 - 585 ML (Comp. B)

Version	Revision Date:	SDS Number:	Date of last issue: 09.06.2022
2.3	11.07.2022	8236679-00006	Date of first issue: 13.04.2021

Result: negative

m-phenylenebis(methylamine):

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 421
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

2,4,6-Tris((Dimethylamino)methyl)phenol:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

p-Toluenesulphonic acid (containing a maximum of 5 % H₂SO₄):

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rabbit
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-PE 510 - 585 ML (Comp. B)

Version 2.3 Revision Date: 11.07.2022 SDS Number: 8236679-00006 Date of last issue: 09.06.2022
Date of first issue: 13.04.2021

Components:

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine:

Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Quartz (SiO₂):

Exposure routes : inhalation (dust/mist/fume)
Target Organs : Lungs
Assessment : Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

Repeated dose toxicity

Components:

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine:

Species : Rat
NOAEL : 10 mg/kg
LOAEL : 60 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks

m-phenylenebis(methylamine):

Species : Rat
NOAEL : 150 mg/kg
Application Route : Ingestion
Exposure time : 28 Days

2,4,6-Tris((Dimethylamino)methyl)phenol:

Species : Rat
NOAEL : 15 mg/kg
Application Route : Ingestion
Exposure time : 43 Days
Method : OECD Test Guideline 422

p-Toluenesulphonic acid (containing a maximum of 5 % H₂SO₄):

Species : Rat
NOAEL : >= 500 mg/kg
Application Route : Ingestion
Exposure time : 28 Days
Method : OECD Test Guideline 407

Quartz (SiO₂):

Species : Humans
LOAEL : 0,053 mg/m³
Application Route : Inhalation
Remarks : These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-PE 510 - 585 ML (Comp. B)

Version	Revision Date:	SDS Number:	Date of last issue: 09.06.2022
2.3	11.07.2022	8236679-00006	Date of first issue: 13.04.2021

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine:

Toxicity to fish	:	LC50 (Leuciscus idus (Golden orfe)): 174 mg/l Exposure time: 48 h Method: DIN 38412
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 31,5 mg/l Exposure time: 24 h Method: DIN 38412
Toxicity to algae/aquatic plants	:	ErC50 (Pseudokirchneriella subcapitata (green algae)): 43,5 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 NOEC (Pseudokirchneriella subcapitata (green algae)): 16 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to microorganisms	:	EC10 (Pseudomonas putida): 72 mg/l Exposure time: 17 h Method: DIN 38 412 Part 8
Toxicity to fish (Chronic toxicity)	:	NOEC: \geq 10,9 mg/l Exposure time: 30 d Species: Danio rerio (zebra fish) Method: OECD Test Guideline 210
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	EC10: 1,02 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-PE 510 - 585 ML (Comp. B)

Version 2.3 Revision Date: 11.07.2022 SDS Number: 8236679-00006 Date of last issue: 09.06.2022
Date of first issue: 13.04.2021

m-phenylenebis(methylamine):

- Toxicity to fish : LC50 (Oryzias latipes (Orange-red killifish)): 87,6 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 15,2 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : ErC50 (Selenastrum capricornutum (green algae)): 33,3 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- NOEC (Selenastrum capricornutum (green algae)): 22,9 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- ErC50 (Selenastrum capricornutum (green algae)): 32,1 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- Toxicity to microorganisms : EC50 : > 1.000 mg/l
Exposure time: 30 min
Method: OECD Test Guideline 209
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 4,7 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

2,4,6-Tris((Dimethylamino)methyl)phenol:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 180 mg/l
Exposure time: 96 h
- Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 84 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- NOEC (Desmodesmus subspicatus (green algae)): 6,25 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- Toxicity to microorganisms : NOEC : 2 mg/l
Exposure time: 28 d
Method: OECD Test Guideline 301D

p-Toluenesulphonic acid (containing a maximum of 5 % H₂SO₄):

- Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): > 325 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-PE 510 - 585 ML (Comp. B)

Version	Revision Date:	SDS Number:	Date of last issue: 09.06.2022
2.3	11.07.2022	8236679-00006	Date of first issue: 13.04.2021

Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 10 - 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): > 1 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC10 : 240 mg/l
Exposure time: 3 h

Quartz (SiO₂):

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 508 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 731 mg/l
Exposure time: 48 h
Remarks: Based on data from similar materials

12.2 Persistence and degradability

Components:

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 7 %
Exposure time: 28 d
Method: Directive 67/548/EEC Annex V, C.4.A.

m-phenylenebis(methylamine):

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 49 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

2,4,6-Tris((Dimethylamino)methyl)phenol:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

p-Toluenesulphonic acid (containing a maximum of 5 % H₂SO₄):

Biodegradability : Result: Readily biodegradable.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-PE 510 - 585 ML (Comp. B)

Version	Revision Date:	SDS Number:	Date of last issue: 09.06.2022
2.3	11.07.2022	8236679-00006	Date of first issue: 13.04.2021

Method: OECD Test Guideline 301B
Remarks: Based on data from similar materials

12.3 Bioaccumulative potential

Components:

2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine:

Partition coefficient: n- : log Pow: -0,3
octanol/water

m-phenylenebis(methylamine):

Partition coefficient: n- : log Pow: 0,18
octanol/water

2,4,6-Tris((Dimethylamino)methyl)phenol:

Partition coefficient: n- : log Pow: 0,219
octanol/water

p-Toluenesulphonic acid (containing a maximum of 5 % H₂SO₄):

Partition coefficient: n- : log Pow: -0,96
octanol/water Method: Regulation (EC) No. 440/2008, Annex, A.8

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-PE 510 - 585 ML (Comp. B)

Version	Revision Date:	SDS Number:	Date of last issue: 09.06.2022
2.3	11.07.2022	8236679-00006	Date of first issue: 13.04.2021

- Product** : Dispose of in accordance with local regulations.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
- Contaminated packaging** : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.
- Waste Code** : The following Waste Codes are only suggestions:
- used product
08 04 09, waste adhesives and sealants containing organic solvents or other hazardous substances
- unused product
08 04 09, waste adhesives and sealants containing organic solvents or other hazardous substances
- uncleaned packagings
15 01 10, packaging containing residues of or contaminated by hazardous substances
- Acc. Packaging Act properly emptied packaging:
Properly emptied, non-contaminated packaging of non-hazardous products can be supplied to a system for the collection of sales packaging.

SECTION 14: Transport information

14.1 UN number or ID number

- ADN** : UN 3259
- ADR** : UN 3259
- RID** : UN 3259
- IMDG** : UN 3259
- IATA** : UN 3259

14.2 UN proper shipping name

- ADN** : AMINES, SOLID, CORROSIVE, N.O.S.
(m-phenylenebis(methylamine), 2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine)
- ADR** : AMINES, SOLID, CORROSIVE, N.O.S.
(m-phenylenebis(methylamine), 2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine)
- RID** : AMINES, SOLID, CORROSIVE, N.O.S.
(m-phenylenebis(methylamine), 2,2,4(or 2,4,4)-Trimethylhexane-1,6-diamine)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-PE 510 - 585 ML (Comp. B)

Version	Revision Date:	SDS Number:	Date of last issue: 09.06.2022
2.3	11.07.2022	8236679-00006	Date of first issue: 13.04.2021

IMDG : AMINES, SOLID, CORROSIVE, N.O.S.
(m-phenylenebis(methylamine), 2,2,4(or 2,4,4)-
Trimethylhexane-1,6-diamine)

IATA : Amines, solid, corrosive, n.o.s.
(m-phenylenebis(methylamine), 2,2,4(or 2,4,4)-
Trimethylhexane-1,6-diamine)

14.3 Transport hazard class(es)

ADN : 8

ADR : 8

RID : 8

IMDG : 8

IATA : 8

14.4 Packing group

ADN
Packing group : II
Classification Code : C8
Hazard Identification Number : 80
Labels : 8

ADR
Packing group : II
Classification Code : C8
Hazard Identification Number : 80
Labels : 8
Tunnel restriction code : (E)

RID
Packing group : II
Classification Code : C8
Hazard Identification Number : 80
Labels : 8

IMDG
Packing group : II
Labels : 8
EmS Code : F-A, S-B

IATA (Cargo)
Packing instruction (cargo aircraft) : 863
Packing instruction (LQ) : Y844
Packing group : II
Labels : Corrosive

IATA (Passenger)
Packing instruction (passenger aircraft) : 859
Packing instruction (LQ) : Y844
Packing group : II
Labels : Corrosive

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-PE 510 - 585 ML (Comp. B)

Version	Revision Date:	SDS Number:	Date of last issue: 09.06.2022
2.3	11.07.2022	8236679-00006	Date of first issue: 13.04.2021

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

Water hazard class (Germany) : WGK 2 obviously hazardous to water
Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-PE 510 - 585 ML (Comp. B)

Version	Revision Date:	SDS Number:	Date of last issue: 09.06.2022
2.3	11.07.2022	8236679-00006	Date of first issue: 13.04.2021

Volatile organic compounds (VOC) content: 21,7 %

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H302 : Harmful if swallowed.
H314 : Causes severe skin burns and eye damage.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H332 : Harmful if inhaled.
H372 : Causes damage to organs through prolonged or repeated exposure if inhaled.
H412 : Harmful to aquatic life with long lasting effects.
EUH071 : Corrosive to the respiratory tract.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Chronic : Long-term (chronic) aquatic hazard
Eye Dam. : Serious eye damage
Skin Corr. : Skin corrosion
Skin Sens. : Skin sensitisation
STOT RE : Specific target organ toxicity - repeated exposure
2004/37/EC : Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.
2004/37/EC / TWA : Long term exposure limit
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships car-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WIT-PE 510 - 585 ML (Comp. B)

Version	Revision Date:	SDS Number:	Date of last issue: 09.06.2022
2.3	11.07.2022	8236679-00006	Date of first issue: 13.04.2021

rying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Acute Tox. 4	H302
Skin Corr. 1A	H314
Eye Dam. 1	H318
Skin Sens. 1	H317

Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN