

DT619 CEM Thermo Anemometer with Wind Speed, CFM, CMM, Air Flow, Temperature

Max/Min/Avg value with relative time stamp

Low battery indication and Auto Power Off

Display Air Flow (CFM/CMM), or Air Velocity plus Temperature simultaneously



Simultaneous display of Air Flow or Air Velocity plus Ambient Temperature

Easy to set Area dimensions (cm²) are stored in the meter's internal memory for the next power on

Resolution of 0.01m/sec

20 points average for Air Flow

Super large LCD Backlit Display

3% velocity accuracy via low friction 2.83"D (72mm) ball bearing vane wheel on 3.9ft (120cm) cable

High Sensitive and Accurate

Air Velocity	Range	Accuracy
m/s(meter per second)	0.40~30.00	±3% ±0.20m/s
ft/min(feet per minute)	80~5900	±3% ±40ft/min
km/h(kilometers per hour)	1.4~108.0	±3% ±0.8km/h
MPH(miles per hour)	0.9~67.0	±3% ±0.4MPH
Knots(nautical miles per hour)	0.8~58.0	±3% ±0.4knots
Air Temperature	-10-60°C(14-140°F)	± 2.0°C(4.0°F)
Air Flow	Range	Area
CFM	0-999900	0-999.9 ft ²
CMM	0-999900	0-999.9 m ²