

DUNE R SASO



DURABLE



EASY MAINTENANCE



ENAMELLED STEEL TANK



HIGH EFFICIENCY INSULATION



FLEXOMIX



EXTERNAL TEMPERATURE REGULATION



5 BOLTS FLANGE



FULL COMFORT

- Double safety thermostat

EVERLASTING QUALITY

- Robust insulation material (polyurethane)
- Magnesium anode to fight corrosion
- High quality enameled tank
- 5 years warranty





EXCLUSIVE DESIGN

- Italian design



5 years warranty

TECHNICAL DATA		DUNE R SASO 50 V	DUNE R SASO 80 V	DUNE R SASO 100 V	DUNE R SASO 50 H	DUNE R SASO 80 H	DUNE R SASO 100 H
Capacity	l	50	80	100	50	80	100
Installation	V	V	V	V	H	H	H
Size		Regular	Regular	Regular	Regular	Regular	Regular
Power	kW	1,2	1,5	1,5	1,2	1,5	1,5
Voltage	V	220	220	220	220	220	220
Heating time (ΔT=45°C)	h,min	2,1'	2,37'	2,46'	2,1'	2,37'	3,19'
Heat dispersion at 65°C	kWh/24h	0,99	1,35	1,56	1,2	1,48	1,65
Max working pressure	bar	8	8	8	8	8	8
Max working temperature	°C	75	75	75	75	75	75
Weight	kg	17	22	26	17	22	26
Class	IP	IPX3	IPX3	IPX3	IPX1	IPX1	IPX1
Frequency	Hz	50/60	50/60	50/60	50/60	50/60	50/60
OVERALL DIMENSIONS							
a	mm	543	748	900	543	748	900
b	mm	380	585	737	-	-	-
c	mm	-	-	-	163	178	178
d	mm	-	-	-	160	335	487
CODE							
		3690000	3690001	3690002	3690003	3690004	3690005



LEGEND
E Cold water inlet G 1/2"
U Hot water outlet G 1/2"