



ITEM NO.	ID	LENGTH	SINGLE LAYER THICKNESS	DOUBLE LAYER THICKNESS	INNER WIRE DIAMETER	MAX WORKING PRESSURE	WORKING TEMPERATURE
FH-6000	60	1-10m	0.02-0.03mm	0.03-0.04mm	0.8mm+/-0.05mm	2000pa	-30°C~+140°C
	80	1-10m	0.02-0.03mm	0.03-0.04mm	0.8mm+/-0.05mm	2000pa	-30°C~+140°C
	102	1-10m	0.02-0.03mm	0.03-0.04mm	0.8mm+/-0.05mm	2000pa	-30°C~+140°C
	127	1-10m	0.02-0.03mm	0.03-0.04mm	0.8mm+/-0.05mm	2000pa	-30°C~+140°C
	152	1-10m	0.02-0.03mm	0.03-0.04mm	0.8mm+/-0.05mm	2000pa	-30°C~+140°C
	165	1-10m	0.02-0.03mm	0.03-0.04mm	0.8mm+/-0.05mm	2000pa	-30°C~+140°C
	203	1-10m	0.02-0.03mm	0.03-0.04mm	0.8mm+/-0.05mm	2000pa	-30°C~+140°C
	254	1-10m	0.02-0.03mm	0.03-0.04mm	0.8mm+/-0.05mm	2000pa	-30°C~+140°C
	305	1-10m	0.02-0.03mm	0.03-0.04mm	0.8mm+/-0.05mm	2000pa	-30°C~+140°C
	315	1-10m	0.02-0.03mm	0.03-0.04mm	0.8mm+/-0.05mm	2000pa	-30°C~+140°C
	352	1-10m	0.02-0.03mm	0.03-0.04mm	0.8mm+/-0.05mm	2000pa	-30°C~+140°C
	402	1-10m	0.02-0.03mm	0.03-0.04mm	0.8mm+/-0.05mm	2000pa	-30°C~+140°C
	450	1-10m	0.02-0.03mm	0.03-0.04mm	0.8mm+/-0.05mm	2000pa	-30°C~+140°C
	500	1-10m	0.02-0.03mm	0.03-0.04mm	0.8mm+/-0.05mm	2000pa	-30°C~+140°C



ITEM NO.	ID	LENGTH	THICKNESS	inner wire diameter	WORKING TEMPERATURE
FH-7000	102	1-10m	0.035mm	0.8mm+/-0.05mm	-30°C~+80°C
	127	1-10m	0.035mm	0.8mm+/-0.05mm	-30°C~+80°C
	152	1-10m	0.035mm	0.8mm+/-0.05mm	-30°C~+80°C
	165	1-10m	0.035mm	0.8mm+/-0.05mm	-30°C~+80°C
	203	1-10m	0.035mm	0.8mm+/-0.05mm	-30°C~+80°C
	254	1-10m	0.035mm	0.8mm+/-0.05mm	-30°C~+80°C
	305	1-10m	0.035mm	0.8mm+/-0.05mm	-30°C~+80°C
	315	1-10m	0.035mm	0.8mm+/-0.05mm	-30°C~+80°C

Usage: Suitable for central air-conditioner, Factory equipment and ventilation for kitchen.